

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

## 1 Identification

- **Product identifier**
- **Trade name:** **QuickStick Duct Liner Adhesive**
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Adhesive.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Ductmate Industries, Inc.  
210 5th St.  
Charleroi, PA 15022  
Phone: 800-990-8459
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)



## 2 Hazard(s) identification

- **Classification of the substance or mixture**
- Flam. Aerosol 1 H222 Extremely flammable aerosol.
- Press. Gas H280 Contains gas under pressure; may explode if heated.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS04 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361 Suspected of damaging fertility or the unborn child.

(Cont'd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

## Trade name: QuickStick Duct Liner Adhesive

(Cont'd. of page 1)

H336 May cause drowsiness or dizziness.

H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

### Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P302+P352 If on skin: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

#### Components:

|          |          |  |        |
|----------|----------|--|--------|
| 110-54-3 | n-hexane | Flam. Liq. 2, H225<br>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304<br>Skin Irrit. 2, H315; STOT SE 3, H336<br>Eye Irrit. 2B, H320 | 25-30% |
| 67-64-1  | Acetone  | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319; STOT SE 3, H336   | 25-30% |
| 74-98-6  | Propane  | Flam. Gas 1, H220<br>Press. Gas, H280  | 20-30% |

#### Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
 For the wording of the listed Hazard Statements, refer to section 16.

(Cont'd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 2)

## 4 First-aid measures

### · Description of first aid measures

#### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses if worn.

#### · After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

#### · Most important symptoms and effects, both acute and delayed:

May cause drowsiness or dizziness.

Breathing difficulty

Coughing

Irritating to eyes and skin.

Dizziness

Disorientation

#### · Danger:

Vapors have narcotic effect.

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure:

Inhalation.

Suspected of damaging fertility or the unborn child.

#### · Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

## 5 Fire-fighting measures

### · Extinguishing media

#### · Suitable extinguishing agents:

Foam

Gaseous extinguishing agents

Carbon dioxide

Water fog / haze

Fire-extinguishing powder

#### · For safety reasons unsuitable extinguishing agents:

Water stream.

Water spray

#### · Special hazards arising from the substance or mixture

(Cont'd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 3)

Extremely flammable aerosol.  
 Danger of receptacles bursting because of high vapor pressure if heated.  
 Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.  
 Wear fully protective suit.

· **Additional information:**

Eliminate all ignition sources if safe to do so.  
 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.  
 Keep away from ignition sources.  
 Protect from heat.  
 Use personal protective equipment as required.  
 For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.  
 For large spills, wear protective clothing.

· **Environmental precautions** Do not allow product to reach sewage system or any water course.

· **Methods and material for containment and cleaning up**

Allow to evaporate.  
 Absorb liquid components with liquid-binding material.  
 Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

## 7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Avoid splashes or spray in enclosed areas.  
 Use only in well ventilated areas.  
 Avoid contact with the eyes and skin.  
 Keep out of reach of children.

· **Information about protection against explosions and fires:**

Extremely flammable aerosol.  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.  
 Do not spray on a naked flame or any incandescent material.  
 Emergency cooling must be available in case of nearby fire.

· **Conditions for safe storage, including any incompatibilities**

(Cont'd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 4)

- **Requirements to be met by storerooms and receptacles:**  
Avoid storage near extreme heat, ignition sources or open flame.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Store away from oxidizers, strong acids, strong bases.
- **Further information about storage conditions:**  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

##### 110-54-3 n-hexane

|               |  |
|---------------|--|
| PEL (USA)     | Long-term value: 1800 mg/m <sup>3</sup> , 500 ppm            |
| REL (USA)     | Long-term value: 180 mg/m <sup>3</sup> , 50 ppm              |
| TLV (USA)     | Long-term value: 176 mg/m <sup>3</sup> , 50 ppm<br>Skin; BEI |
| EL (Canada)   | Long-term value: 20 ppm<br>Skin                              |
| EV (Canada)   | Long-term value: 176 mg/m <sup>3</sup> , 50 ppm              |
| LMPE (Mexico) | Long-term value: 50 ppm<br>PIEL, IBE                         |

##### 67-64-1 Acetone

|               |   |
|---------------|---|
| PEL (USA)     | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm  |
| REL (USA)     | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm  |
| TLV (USA)     | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 594 mg/m <sup>3</sup> , 250 ppm<br>BEI |
| EL (Canada)   | Short-term value: 500 ppm<br>Long-term value: 250 ppm   |
| EV (Canada)   | Short-term value: 750 ppm<br>Long-term value: 500 ppm   |
| LMPE (Mexico) | Short-term value: 750 ppm<br>Long-term value: 500 ppm<br>A4, IBE  |

##### 74-98-6 Propane

|             |  |
|-------------|--|
| PEL (USA)   | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm   |
| REL (USA)   | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm   |
| TLV (USA)   | refer to Appendix F in TLVs&BEIs book; D, EX         |
| EL (Canada) | Long-term value: 1000 ppm                            |
| EV (Canada) | Long-term value: 1,000 ppm<br>revoked as of 01/01/18 |

(Cont'd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 5)

LMPE (Mexico) | Long-term value: 1000 ppm

· **Ingredients with biological limit values:**

**110-54-3 n-hexane**

BEI (USA) | 0.4 mg/L  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: 2,5-Hexanedione without hydrolysis

**67-64-1 Acetone**

BEI (USA) | 50 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

· **Exposure controls**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

· **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Solvent resistant protective clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

· **Risk management measures** No relevant information available.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

Form: Aerosol

Color: Colorless

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

(Cont'd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 6)

|   |  |
|---|--|
| · <b>pH-value:</b>                                | Not determined.  |
| · <b>Melting point/Melting range:</b>             | Not applicable, as aerosol.  |
| · <b>Boiling point/Boiling range:</b>             | Not applicable, as aerosol.  |
| · <b>Flash point:</b>                             | Extremely flammable aerosol.   |
| · <b>Flammability (solid, gaseous):</b>           | Not applicable.  |
| · <b>Auto-ignition temperature:</b>               | Not determined.  |
| · <b>Decomposition temperature:</b>               | Not determined.  |
| · <b>Danger of explosion:</b>                     | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · <b>Explosion limits</b><br><b>Lower:</b>        | Not determined.  |
| <b>Upper:</b>                                     | Not determined.  |
| · <b>Oxidizing properties:</b>                    | Non-oxidizing.   |
| · <b>Vapor pressure:</b>                          | Not determined.  |
| · <b>Density:</b><br><b>Relative density:</b>     | Not determined.  |
| <b>Vapor density:</b>                             | Not determined.  |
| <b>Evaporation rate:</b>                          | Not applicable.  |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.  |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.  |
| · <b>Viscosity</b><br><b>Dynamic:</b>             | Not determined.  |
| <b>Kinematic at 40 °C (104 °F):</b>               | <20.5 mm <sup>2</sup> /s   |
| · <b>Other information</b>                        | No relevant information available.   |

### 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
Danger of receptacles bursting because of high vapor pressure if heated.
- **Possibility of hazardous reactions**  
Develops readily flammable gases / fumes.  
Reacts with oxidizing agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.  
Extremely flammable aerosol.  
Toxic fumes may be released if heated above the decomposition point.  
Reacts with strong acids and alkali.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers, strong bases, strong acids

(Cont'd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 7)

· **Hazardous decomposition products**

Under fire conditions only:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

· **Information on toxicological effects**

- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** Based on available data, the classification criteria are not met.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Inhalation.  
Eye contact.  
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:**  
May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure:  
Inhalation.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

## 12 Ecological information

· **Toxicity**

- **Aquatic toxicity** Toxic to aquatic life with long lasting effects.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information**

- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Cont'd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 8)

- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

## 13 Disposal considerations

### · Waste treatment methods

#### · Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

### · Uncleaned packagings

- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

### · UN-Number

· DOT, ADR, IMDG, IATA UN1950

### · UN proper shipping name

· DOT Aerosols  
 · ADR, IMDG AEROSOLS  
 · IATA Aerosols, flammable

### · Transport hazard class(es)

#### · DOT



· Class 2.1  
 · Label 2.1

#### · ADR



· Class 2 5F  
 · Label 2.1

#### · IMDG, IATA



· Class 2.1  
 · Label 2.1

(Cont'd. on page 10)

**Safety Data Sheet**






acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 9)

|   |   |
|---|---|
| · <b>Packing group</b>  | Aerosols are not assigned a packing group.                      |
| · <b>Environmental hazards</b>  | Product contains environmentally hazardous substances: n-hexane |
| · <b>Marine pollutant:</b>  |   |
|  Yes   |   |
| · <b>Special precautions for user</b>   | Warning: Gases  |
| · <b>Danger code (Kemler):</b>  | -   |
| · <b>EMS Number:</b>  | F-D,S-U   |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>  | Not applicable.   |
| · <b>Transport/Additional information:</b>  |   |
| · <b>DOT</b>  |   |
|  Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.  |   |
| · <b>ADR</b>  |   |
|  Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L. |   |
| · <b>IMDG</b>   |   |
|  Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L. |   |
| · <b>IATA</b>   |   |
|  Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L. |   |

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

(Cont'd. on page 11)

**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 10)

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3 | n-hexane

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

74-98-6 | Propane

10000

· **Proposition 65 (California)**· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

110-54-3 | n-hexane

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

110-54-3 | n-hexane

II

67-64-1 | Acetone

I

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety &amp; Health Administration

Flam. Gas 1: Flammable gases – Category 1

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

(Cont'd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: May 16, 2018

Revision: May 16, 2018

**Trade name: QuickStick Duct Liner Adhesive**

(Cont'd. of page 11)

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1

• **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sor\\_internet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)