

## Praxair Material Safety Data Sheet

### 1. Chemical Product and Company Identification

<b>Product Name:</b> Inert Gas/Nitrous Oxide Mixture	<b>Trade Name:</b> Inert Gas/Nitrous Oxide Mixture
<b>Product Use:</b> Not available.	
<b>Chemical Name:</b> Inert Gas/Nitrous Oxide Mixture	<b>Synonym:</b> Not available.
<b>Chemical Formula:</b> Not available.	<b>Chemical Family:</b> Not applicable.
<b>Telephone:</b> <b>Emergencies:</b> * 1-800-363-0042	<b>Supplier /Manufacture:</b> Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2  <b>Phone:</b> 905-803-1600 <b>Fax:</b> 905-803-1682

*\*Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

### 2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD <sub>50</sub> (Species & Routes)	LC <sub>50</sub> (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Nitrous oxide	0.0001-0.0999	10024-97-2	Not applicable.	Not available.	50 ppm
And contains one or more of the following gases:					
Argon	99.9001-99.9999	7440-37-1	Not applicable.	Not available.	Simple asphyxiant.
Helium	99.9001-99.9999	7440-59-7	Not applicable.	Not available.	Simple asphyxiant.
Krypton	99.9001-99.9999	7439-90-9	Not applicable.	Not available.	Simple asphyxiant.
Neon	99.9001-99.9999	7440-01-9	Not applicable.	Not available.	Simple asphyxiant.
Nitrogen	99.9001-99.9999	7727-37-9	Not applicable.	Not available.	Simple asphyxiant.
Xenon	99.9001-99.9999	7440-63-3	Not applicable.	Not available.	Simple asphyxiant.

### 3. Hazards Identification

#### Emergency Overview

**CAUTION!** High-pressure gas. Can cause rapid suffocation. May cause dizziness and drowsiness. Self-contained breathing apparatus may be required by rescue workers.

**ROUTES OF EXPOSURE:** Inhalation.

**EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:**

**INHALATION:** Asphyxiant. Moderate concentrations may cause headache, drowsiness, dizziness, stinging of the nose and throat, excitation, rapid breathing, excess salivation, vomiting and unconsciousness. This product contains traces of Nitrous Oxide which may cause incoordination and narcosis, and clinical anaesthesia. Lack of oxygen can kill.

**SKIN CONTACT:** No evidence of adverse effects from available information.

**SKIN ABSORPTION:** No evidence of adverse effects from available information.

**SWALLOWING:** A highly unlikely route of exposure. This product is a gas at room temperature and pressure.

**EYE CONTACT:** No evidence of adverse effects from available information.

**EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:**

Metabolic injury to the nervous system has resulted from frequent exposure to anaesthetic concentrations of Nitrous Oxide.

**OTHER EFFECTS OF OVEREXPOSURE:**

This product is an asphyxiant. Exposure to Nitrous Oxide has produced embryo fetal toxicity in laboratory animals. Exposure to Nitrous Oxide may be associated with an increased incidence of abortion in humans.

**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:**

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:**

None currently known.

**CARCINOGENICITY:**

Classified A4 (Not classifiable for human or animal.) by ACGIH [Nitrous oxide].

**4. First Aid Measures**

**INHALATION:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

**SKIN CONTACT:**

Wash with soap and water.

**SWALLOWING:**

This product is a gas at normal temperature and pressure.

**EYE CONTACT:**

Flush with water.

**NOTES TO PHYSICIAN:**

*There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.*

**5. Fire Fighting Measures**

<b>FLAMMABLE :</b>	No.	<b>IF YES, UNDER WHAT CONDITIONS?</b>	Not applicable.
<b>FLASH POINT (test method)</b>	Not applicable.	<b>AUTOIGNITION TEMPERATURE</b>	Not applicable.

Product Name: Inert Gas/Nitrous Oxide  
Mixture

MSDS# E-6784-I

Date: Oct. 15, 2016

**FLAMMABLE LIMITS  
IN AIR, % by volume:**

**LOWER:** Not applicable.

**UPPER:** Not applicable.

**EXTINGUISHING MEDIA:**

This mixture cannot catch fire. Use media appropriate for surrounding fire.

**SPECIAL FIRE FIGHTING PROCEDURES:**

**CAUTION!** Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool; then move them away from fire area if without risk.

**UNUSUAL FIRE AND EXPLOSION HAZARD:**

Gas mixture (high pressure gas) cannot catch fire. Container may rupture due to heat of fire. No part of a container should be subjected to a temperature higher than 52 C. Most containers are provided with a pressure relief device designed to vent contents when they are exposed to elevated temperature.

**HAZARDOUS COMBUSTION PRODUCTS:**

Not applicable.

**SENSITIVITY TO IMPACT:**

Avoid impact against container.

**SENSITIVITY TO STATIC DISCHARGE:**

Not available.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

**CAUTION!** **High-pressure gas.** Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off flow if you can do so without risk. Ventilate area or move cylinder to a well-ventilated area. Test for sufficient oxygen, especially in confined spaces, before allowing reentry of personnel.

**WASTE DISPOSAL METHOD:**

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

## 7. Handling and Storage

**PRECAUTIONS TO BE TAKEN IN STORAGE:**

Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

**PRECAUTIONS TO BE TAKEN IN HANDLING:**

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to Section 16 for the address and phone number along with a list of other available publications.

**OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:**

**High pressure gas.** Use piping and equipment adequately designed to withstand pressures to be encountered. **Gas can cause rapid suffocation due to oxygen deficiency.** Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, provincial, and local laws, then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

**8. Exposure Controls/Personal Protection**

**VENTILATION/ENGINEERING CONTROLS:**

**LOCAL EXHAUST:** Preferred.

**MECHANICAL (general):** Acceptable.

**SPECIAL:** Not applicable.

**OTHER:** Not applicable.

**PERSONAL PROTECTION:**

**RESPIRATORY PROTECTION:** Select in accordance with provincial regulations, local bylaws or guidelines. Selection should also be based on the current CSA standard Z94.4, "Selection, Care and Use of Respirators". Respirators should also be approved by NIOSH and MSHA.

**SKIN PROTECTION:** Preferred for cylinder handling.

**EYE PROTECTION:** Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

**OTHER PROTECTIVE EQUIPMENT:** Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

**9. Physical and Chemical Properties**

<b>PHYSICAL STATE:</b> Gas.	<b>FREEZING POINT:</b> Not available.	<b>pH:</b> Not available.
<b>BOILING POINT:</b> Not available.	<b>VAPOUR PRESSURE:</b> Not applicable.	<b>MOLECULAR WEIGHT:</b> Not applicable.
<b>SPECIFIC GRAVITY: LIQUID ( Water = 1)</b> Not available.	<b>SOLUBILITY IN WATER:</b> Not available.	
<b>SPECIFIC GRAVITY: VAPOUR (air = 1)</b> Not available.	<b>EVAPORATION RATE (Butyl Acetate=1):</b> Not available.	<b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b> Not applicable.
<b>VAPOUR DENSITY:</b> Not available.	<b>% VOLATILES BY VOLUME:</b> Not available.	<b>ODOUR THRESHOLD:</b> Not available.

**APPEARANCE & ODOUR:** Colourless gas at normal temperature and pressure.

### 10. Stability and Reactivity

<b>STABILITY:</b>	The product is stable.
<b>CONDITIONS OF CHEMICAL INSTABILITY:</b>	See Section 7.
<b>INCOMPATIBILITY (materials to avoid):</b>	None currently known. Gas is chemically inert.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	None.
<b>HAZARDOUS POLYMERIZATION:</b>	Will not occur.
<b>CONDITIONS OF REACTIVITY:</b>	None currently known.

### 11. Toxicological Information

See section 3.

### 12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG regulations.

### 13. Disposal Considerations

**WASTE DISPOSAL METHOD:** Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

### 14. Transport Information

**TDG/IMO SHIPPING NAME:** Compressed gas, n.o.s. (indicate the most important inert component)

**HAZARD CLASS:** CLASS 2.2: Non-flammable non-corrosive and non-toxic gas

**IDENTIFICATION #:** UN1956

**PRODUCT RQ:**  
Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more

**SHIPPING LABEL(s):** Non-flammable, non-corrosive and non-toxic gas

**PLACARD (when required):** Non-flammable, non-corrosive and non-toxic gas

#### SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

### 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

**Canada (DSL)** This product is on the DSL list

**WHMIS (Canada)** Class A: Compressed gas.

**International Regulations**

Product Name: Inert Gas/Nitrous Oxide  
Mixture

MSDS# E-6784-I

Date: Oct. 15, 2016

**EINECS** Not available.

**DSCL (EEC)** This product is not classified according to the EU regulations.

**International Lists** No products were found.

## 16. Other Information

### MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

### HAZARD RATING SYSTEM:

#### HMIS RATINGS:

HEALTH 0

FLAMMABILITY 0

PHYSICAL HAZARD 2

### STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

**THREADED:** CGA-590

**PIN-INDEXED YOKE:** Not available.

**ULTRA-HIGH-INTEGRITY CONNECTION:** Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: [www.cganet.com](http://www.cganet.com).

- AV-1 Safe Handling and Storage of Compressed Gas
- P-1 Safe Handling of Compressed Gases in Containers
- P-14 Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmospheres
- SB-2 Oxygen-Deficient Atmospheres
- V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
- V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
- Handbook of Compressed Gases, Fifth Edition

**For more indepth information for each component, refer to the pure product MSDS.**

**The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.**

### PREPARATION INFORMATION:

**DATE:** October 15, 2016

**DEPARTMENT:** Safety and Environmental Services

**TELEPHONE:** 905-803-1600

**Product Name:** Inert Gas/Nitrous Oxide  
Mixture

**MSDS#** E-6784-I

**Date:** Oct. 15, 2016

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

*Praxair* and the *Flowing Airstream* design are trademarks of  
Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.  
1 City Centre Drive  
Suite 1200  
Mississauga, ON L5B 1M2

Copyright © 2016, Praxair Canada Inc.

**Page 7 of 7**