

EXTREME-WEATHER WINDOW AND DOOR INSULATING FOAM SEALANT — CF-I XTW WD



Applications for use

- Insulating window and door joints
- Acoustic insulation — shutter boxes, cooling and heating lines, wood floors, insulation panels, air conditioning and ventilation channels
- Attics
- Drywall joints
- Filling — wall openings, pipe penetrations, panels, risers, ducts and prefabricated elements
- Ventilation ducts
- Bathtub cavities
- Gaps and cracks
- General-purpose construction foam

Advantages

- Seals, insulates and fills
- Reliable over a wide temperature range
- Precise dispensing and volumetric control
- Simple to apply
- High thermal insulation
- Good soundproofing

Installation instructions

- See Hilti Literature or third-party listings for complete application and installation details

Technical Data

Application temperature range	-15 °C to +35 °C
Temperature resistance range	-40 °C to + 80 °C
Flame spread	0
Smoke developed	0
R Value (ASTM C 518)	3.29 per inch
Approximate cure schedule (at 23°C / 50% rel. humidity)	<ul style="list-style-type: none"> • Tack free after 10 mins • Ready to cut after 25 mins
Ready to cut time (at 23°C / 50% rel. humidity)	25 mins
Tested in Accordance with	AAMA 812 ASTM E90 ASTM E96 ASTM G21 ASTM E331 ASTM E2178 ASTM C518 ULC S102
