



Material Safety Data Sheet

GLD ULTRA FLAT WH 94500

1. Product and company identification

Product name : GLD ULTRA FLAT WH 94500
Synonym : Not available.
Trade name : Not available.
Material uses : Not available.
Manufacturer : PPG Architectural Coatings Canada Inc.
2505 De la Métropole,
Longueuil, QC, J4G 1E5
Validation date : **2013-10-24.**
Print date : 2013-10-24.
Responsible name : Regulatory Department
In case of emergency : 450-442-7923
8:00 - 17:00
Product use : Water based coating

2. Hazards identification

Emergency overview : WARNING!



CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA.

Severely irritating to eyes. Irritating to skin. Slightly irritating to the respiratory system. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not get in eyes. Avoid contact with skin and clothing. Contains material that may cause target organ damage, based on animal data. Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure. Contains material which may cause birth defects, based on animal data. Avoid exposure during pregnancy. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Medical conditions aggravated by over-exposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
sodium potassium aluminum silicate	37244-96-5	10 - 30
titanium dioxide	13463-67-7	5 - 10
calcium carbonate	471-34-1	5 - 10
natural ground diatomaceous earth - amorphous silica (pig white 27)	61790-53-2	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6 . Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Product name

titanium dioxide

Exposure limits

OSHA PEL (United States, 6/2010).

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

OSHA PEL 1989 (United States, 3/1989).

TWA: 10 mg/m³ 8 hour(s). Form: Total dust

ACGIH TLV (United States, 1/2011). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A - Carcinogens.

TWA: 10 mg/m³ 8 hour(s).

calcium carbonate

OSHA PEL (United States, 6/2010).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

OSHA PEL 1989 (United States, 3/1989).

TWA: 6 mg/m³ 8 hour(s).

OSHA PEL Z3 (United States, 9/2005).

TWA: 20 mppcf 8 hour(s).

NIOSH REL (United States, 6/2009).

TWA: 6 mg/m³ 10 hour(s).

OSHA PEL Z3 (United States, 9/2005). Notes: 80/(%SiO₂)

TWA: 80 mg/m³ 8 hour(s).

Kieselguhr

Consult local authorities for acceptable exposure limits.

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

8 . Exposure controls/personal protection

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Other protection** : Not available.
- Personal protective equipment (Pictograms)** : Not available.

9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Not applicable.
- Auto-ignition temperature** : Not available.
- Color** : Various
- Odor** : Characteristic
- pH** : 9
- Boiling/condensation point** : 100°C (212°F)
- Melting/freezing point** : -5°C (23°F)
- Specific gravity** : 1.39
- Vapor pressure** : 3.3 kPa (25 mm Hg) [20°C]
- Vapor density** : >1 [Air = 1]
- Volatility** : 69.07% (v/v), 49.73% (w/w)
- Odor threshold** : Not available.
- Evaporation rate** : 0.05 (butyl acetate = 1)
- Dispersibility properties** : Easily dispersible in the following materials: cold water.
- Partition coefficient: n-octanol/water** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Dynamic: 1500 mPa·s (1500 cP)

10 . Stability and reactivity

Stability	: The product is stable.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: No specific data.
Materials to avoid	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Conditions of reactivity	: Slightly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Not available.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-	LD Intratracheal	Rat	>100 ug/kg	-
-	TDLo Intratracheal	Rat	5 mg/kg	-
-	TDLo Intratracheal	Rat	1.6 mg/kg	-
-	TDLo Intratracheal	Rat	1.25 mg/kg	-
-	TDLo Oral	Rat	60 g/kg	-
-	LD50 Oral	Rat	6450 mg/kg	-
-	TDLo Oral	Rat	60 g/kg	-
-	TDLo Oral	Rat	10 mg/kg	-

Chronic toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
calcium carbonate	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-

Sensitizer

Product/ingredient name	Route of exposure	Species	Result
Not available.			

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
titanium dioxide	A4	2B	-	+	-	-
Kieselguhr	-	3	-	-	-	-

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Not available.			

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

11 . Toxicological information

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
-------------------------	-------------------	-----------	-------------------	---------	------	----------

Not available.

Synergistic products : Not available.

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.
Ingestion : No known significant effects or critical hazards.
Skin : Irritating to skin.
Eyes : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.
Carcinogenicity : Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : Contains material which may cause birth defects, based on animal data.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
Target organs : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Ingestion : Adverse symptoms may include the following:
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Skin : Adverse symptoms may include the following:
 irritation
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Eyes : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
-------------------------	------	--------	---------	----------

12 . Ecological information

Algae - Pseudokirchneriella subcapitata - Exponential growth phase	-	Acute EC50 35.9 mg/L Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
Algae - Pseudokirchneriella subcapitata - Exponential growth phase	-	Acute EC50 5.83 mg/L Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	-	Acute LC50 5.5 ppm Fresh water	Daphnia - Water flea - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
Fish - Fundulus heteroclitus	-	Acute LC50 >1000000 ug/L Marine water	Fish - Mummichog - Fundulus heteroclitus	96 hours
Algae - Pseudokirchneriella subcapitata - Exponential growth phase	-	Chronic NOEC 95 mg/L Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
Algae - Pseudokirchneriella subcapitata - Exponential growth phase	-	Chronic NOEC 10.1 mg/L Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
Algae - Pseudokirchneriella subcapitata - Exponential growth phase	-	Chronic NOEC 0.984 mg/L Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
Fish - Gambusia affinis - Adult	-	Acute LC50 >56000000 ug/L Fresh water	Fish - Western mosquitofish - Gambusia affinis - Adult	96 hours
Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	-	Chronic NOEC 61 mg/g Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	28 days
Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	-	Chronic NOEC 61 mg/g Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	42 days
Fish - Oncorhynchus mykiss - Juvenile	-	Chronic NOEC 61	Fish - Rainbow	35 days

12 . Ecological information

(Fledgling, Hatchling, Weanling)

mg/g Fresh water trout,donaldson
trout -
Oncorhynchus
mykiss - Juvenile
(Fledgling,
Hatchling,
Weanling)

- Conclusion/Summary** : Not available.
Bioconcentration factor : Not available.
Mobility : Not available.
Toxicity of the products of biodegradation : Not available.
Other adverse effects : No known significant effects or critical hazards.

13 . Disposal considerations

- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Waste stream** : Not available.
- Disposal should be in accordance with applicable regional, national and local laws and regulations.**
- Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.**

14 . Transport information

TDG Classification Not regulated.

IMDG Class Not regulated.

IATA-DGR Class Not regulated.

15 . Regulatory information

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Label requirements : CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.) :

Health	*	2
Flammability		1
Physical hazards		0

15 . Regulatory information

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

16 . Other information

Version : 9

Notice to reader

The manufacturer hereby declares that the information disclosed herein have been based on our raw material suppliers' data, information and notification. Such raw materials are being used as components in the manufacturing of the product. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Materials used may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. The product must be handled with care and it is recommended to use all the required measures in order to ensure the protection and safety of any person using or handling the product. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.