


214 COLLEGE ST, TORONTO, ON M5T 3A1



NOTE:

THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH MECHANICAL, COMMUNICATIONS, SECURITY AND AV DRAWINGS TO ENSURE ALL RELEVANT DIVISION 26 SCOPE OF WORK (CONDUIT, WIRING, PATHWAYS, ETC.) IS CAPTURED. READ ALL DRAWINGS AND SPECIFICATIONS OF ALL DISCIPLINES PRIOR TO BID.



SEAL :	
--------	--



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AND
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS :

**COVER & DRAWING LIST -
ELECTRICAL**

PROJECT NUMBER :	21590.003
DRAWING SCALE :	

DRAWN BY : Author			CHECKED BY : Checker	DATE: Issue Date
----------------------	--	--	-------------------------	---------------------

SHEET NO :		REV
------------	--	-----

E000	6
-------------	----------

13 SECURITY ABBREVIATIONS
E010


SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	WALL MOUNTED DATA AND VOIP DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		EMERGENCY PHONE SYSTEM OUTLET(S) 1 ANALOG VOICE CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION
	WALL MOUNTED ABOVE COUNTER DATA AND VOIP DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		COMMUNICATIONS INTERCOM OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION
	WALL MOUNTED ANALOG VOICE OUTLET(S) 1 ANALOG VOICE CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		COMMUNICATIONS MASTER INTERCOM WALL MOUNTED DATA AND VOIP DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION
	WALL MOUNTED ABOVE COUNTER VOICE OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		POCKET MONITORING DATA AND VOIP DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION
	FLOOR MOUNTED DATA AND VOIP DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		CANAL CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION
	FLOOR MOUNTED ANALOG VOICE OUTLET(S) 1 ANALOG VOICE CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		MAIN CABLE SUPPORT ROUTE FOR COMMUNICATIONS CABLEING
	FLOOR MOUNTED DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		COMMUNICATIONS BOX
	FLOOR MOUNTED ANALOG VOICE OUTLET(S) 1 ANALOG VOICE CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		POWER ZONE BOX
	FLOOR MOUNTED DATA AND VOIP DATA OUTLET(S) 2 DATA CABLES UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		TELEPHONE ZONE BOX
	FLOOR MOUNTED ANALOG VOICE OUTLET(S) 1 ANALOG VOICE CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		FEED POINT FOR COMMUNICATIONS CABLEING, LETTER DENOTES FEED LOCATION W = WALL, F = FLOOR, P = PAC PANEL, W = WIREMOLD
	CEILING MOUNTED DATA OUTLET(S) 1 DATA CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		20 DATA CABLES
	CEILING MOUNTED ANALOG VOICE OUTLET(S) 1 ANALOG VOICE CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		THREE (3) DATA CABLES
	WALL MOUNTED DATA OUTLET(S) FOR INDIVIDUALS 1 DATA CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		
	WALL MOUNTED DATA OUTLET(S) FOR INDIVIDUALS 1 DATA CABLE UNLESS OTHERWISE NOTED CABLE TYPE AS PER SPECIFICATION		

14 DATA/COMMUNICATIONS
E010





















SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	AUDIO VISUAL SYSTEM		PROJECTOR
	DEVICE IDENTIFICATION NUMBER		PROJECTOR ON LIFT
	AV EQUIPMENT RACK		PROJECTION SCREEN
	RACK TO DESIGNATION: "AV" = FREE STANDING EQUIPMENT "C" = CEILING RACK "WC" = RACK ON CASTERS		CEILING RECESSED SPEAKER
	WALL MOUNT FLAT PANEL DISPLAY		"TAG" DESIGNATION "S" = AV SPEAKER
	DISPLAY "TAG" DESIGNATION: "T" = TELEVISION DISPLAY "I" = INTERACTIVE DISPLAY "D" = DIGITAL SIGNAGE DISPLAY "W" = MEDIA WALL DISPLAYS SEE DRAWINGS FOR QUANTITIES		SURFACE MOUNT SPEAKER
	CEILING MOUNT FLAT PANEL DISPLAY		"TAG" DESIGNATION "S" = AV SPEAKER
	DISPLAY "TAG" DESIGNATION: "PND" = PICTURE DUAL FLAT PANEL DISPLAY "DUAL" = PICTURE DUAL FLAT PANEL DISPLAYS		WALL MOUNT ANTENNA
	NOTE: "XX" DENOTES SCREEN SIZE (INCHES)		"TAG" DESIGNATION: "ANT" = MICROPHONE ANTENNA "HA" = HEARING ASSIST ANTENNA
	WALL MOUNT AV INTERFACE		CEILING MOUNT ANTENNA
	"TAG" DESIGNATION: "TRB" = ROOM BOOKING DISPLAY "MCD" = MEETING ROOM DISPLAY "CTL" = TOUCH CONTROL PANEL		"TAG" DESIGNATION: "ANT" = MICROPHONE ANTENNA "HA" = HEARING ASSIST ANTENNA
	NOTE: "XX" DENOTES SCREEN SIZE (INCHES)		CEILING MOUNT MICROPHONE
	BUTTON CONTROL PANEL BY AUDIOVISUAL CONTRACTOR		
	3/8" VIDEO CONTROL "V" = VIDEO CONTROL (FOR PROJECTION SCREENS)		AV MOUNTING
	FLOORBOX CONNECTION FOR TABLETOP CONNECTIVITY		AV INPUT PULL BOX (1) = 1 GANG (2) = 2 GANG (3) = 3 GANG
	WALL MOUNT AV CAMERA		AV BACKBOX (1) = 1 GANG (2) = 2 GANG (3) = 3 GANG
	CEILING MOUNT AV CAMERA		AV CABLE PULL BOX
			SIZE DESIGNATION: "X06" = 6"X6" AV CABLE PULL BOX "12X12" = 12X12" AV CABLE PULL BOX

NOTE: NOT ALL SYMBOLS APPLY. REFER TO DRAWINGS





























15 A/V LEGEND
E010



DESIGNATION DIAGRAM




































SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
ACCESS CONTROL			
	ACCESS CONTROL SYSTEM PANEL		KEY SWITCH
	ACCESS CONTROL SYSTEM SERVER		LATCH BOLT MONITOR
	AUTOMATIC DOOR OPERATOR		LATCH REQUEST TO EXIT
	CARD READER (SALTO)		MAGLOCK KEY RESET SWITCH
	CARD READER (HID R40)		MAGNETIC DOOR HOLD/OPEN DEVICE
	CENTRAL MANAGEMENT STATION		MAGNETIC LOCK
	DOOR ALARM		MOTION REQUEST TO EXIT
	DOOR CONTACT		POWER SUPPLY CONTROL UNIT
	ELECTRIC DOOR HOLD/OPEN DEVICE		PUSH BUTTON DOOR OPERATOR
	ELECTRIC LATCH RETRACTION		PUSH BUTTON REQUEST TO EXIT
	ELECTRIC MORTISE LOCK		REMOTE RELEASE
	ELECTRIC STRIKE		RF NODE
	GATEWAY		RF RECEIVER
	IP DOOR CONTROLLER		SECURITY DOOR TAG. XX DENOTES TYPE
	KEY ENCODER		WIRELESS LOCK
REAL TIME LOCATING SYSTEM (RTLTS)			
	LOW FREQUENCY EXCITER		RF READER MASTER
	INFRARED READER		RF READER
	REMOTE DISPLAY UNIT		RF ETHERNET READER
	LOCAL AREA RECEIVER		RF LONG RANGE READER

11 SECURITY LEGEND 1 OF 2
E010

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
ELECTRONIC PERSONAL PROTECTION			
	EMERGENCY PHONE STATION		DURABLE ALARM STATION
	STROBE LIGHT		PANIC ALARM RECEIVER
	PANIC BUTTON		ASSISTANCE REQUIRED SIGNAL
INTERCOM LEGEND			
	INTERCOM		MASTER INTERCOM
	ENTRY PHONE CONSOLE		
VIDEO SURVEILLANCE			
	FIXED CAMERA		VIDEO SURVEILLANCE SYSTEM SERVER
	PAN-TILT-ZOOM CAMERA		POWER INJECTOR
	PERSONAL COMPUTER		VIDEO MONITOR
	COMPUTER MONITOR		FIXED VIDEO SURVEILLANCE CAMERA HORIZONTAL ANGLE OF VIEW
	DIGITAL VIDEO RECORDER		LCD MONITOR SIZE AS INDICATED
	NETWORK VIDEO RECORDER		
INTRUSION DETECTION			
	SIREN		INTRUSION DETECTION SYSTEM PANEL
	BREAK GLASS SENSOR		POWER SUPPLY
	MOISTURE SENSOR		WALL MOUNTED SECURITY MOTION SENSOR
	KEYPAD		CEILING MOUNTED SECURITY 90° MOTION SENSOR

NOTE: NOT ALL SYMBOLS APPLY. REFER TO DRAWINGS

12 SECURITY LEGEND 2 OF 2
FD10

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
SIGNALING DEVICES			
	CEILING MOUNTED HORN		WALL MOUNTED FIRE ALARM BELL 103mm (4 1/8") UNLESS OTHERWISE NOTED
	WALL MOUNTED HORN		WALL MOUNTED FIRE ALARM BELL +STROBE COMBINATION
	CEILING MOUNTED DOUBLE SIDED HORN		SPEAKER HORN
	WALL MOUNTED DOUBLE SIDED HORN		CEILING MOUNTED EMERGENCY EVACUATION SPEAKER
	CEILING MOUNTED HORN+STROBE COMBINATION, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED		WALL MOUNTED EMERGENCY EVACUATION SPEAKER
	WALL MOUNTED HORN+STROBE COMBINATION, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED		CEILING MOUNTED FIRE ALARM BELL +STROBE COMBINATION, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED
	CEILING MOUNTED DOUBLE SIDED HORN+STROBE COMBINATION, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED		WALL MOUNTED EMERGENCY EVACUATION SPEAKER +STROBE COMBINATION, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED
	WALL MOUNTED DOUBLE SIDED HORN+STROBE COMBINATION, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED		CEILING MOUNTED FIRE ALARM BELL, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED
	MINI HORN		WALL MOUNTED FIRE ALARM BELL, STROBE INTENSITY TO BE MIN. 15CD UNLESS OTHERWISE NOTED
ANCILLARY DEVICES			
	ISOLATION MODULE		MONITORING MODULE FOR ALARM OR SUPERVISORY
	FIELD INSTALLED ADDRESSABLE CONTROL PANEL		TROUBLE AND ALARM CONNECTION TO PRE-ACTION CONTROL PANEL
	"FIRE, DO NOT ENTER" SIGN		FLOOR MOUNTED DOOR HOLD OPEN DEVICE
	FIRE ALARM GRAPHIC (PASSIVE/ACTIVE)		WALL MOUNTED DOOR HOLD OPEN DEVICE
	VIDEO DISPLAY TERMINAL, FOR BUILDING OPERATIONS PERSONNEL		FIRE ALARM PANEL CONTROL, DGP OR ANNUNCIATOR AS NOTED
	FIRE FIGHTERS HAND SET		END-OF-LINE RESISTOR TERMINAL
	FIRE ALARM SHUT DOWN		SMOKE DAMPER, USED IN CONJUNCTION WITH MONITORING DEVICE FOR POSITION ANNUNCIATION AND CONTROL DEVICE
	FIRE ALARM START UP		10 MINUTE SILENCE SWITCH FOR SPEAKERS IN BUSES
	REMOTE TESTING STATION FOR DUCT SMOKE DETECTORS		
NOTE: NOT ALL SYMBOLS APPLY. REFER TO DRAWINGS			

7 FIRE ALARM LEGEND 2 OF 2
E010

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	ISOLATION TRANSFORMER - DELTA-WYE UNLESS OTHERWISE NOTED.		AUTO-TRANSFORMER
			BATTERY
	ISOLATION TRANSFORMER WITH ELECTROSTATIC SHIELD - DELTA-WYE UNLESS OTHERWISE NOTED.		CONTACTOR
	MOLDED CASE CIRCUIT BREAKER, SIZE AS SHOWN.		CURRENT TRANSFORMER
	LOW VOLTAGE, DRAW-OUT CIRCUIT BREAKER, TRIP PLUG AND FRAME SIZE AS SHOWN.		GROUND FAULT ALARM RELAY
	DRAW-OUT VACUUM CIRCUIT BREAKER, PROTECTIVE RELAY FUNCTIONS AND FRAME SIZE AS SHOWN.		IP BASED POWER QUALITY DIGITAL METER PROVIDE SUFFICIENT CONDUIT TO NEAREST TELECOM ROOM
	FIBERGLASS LOAD BREAK ISOLATION SWITCH, VOLTAGE, FUSE AND FRAME SIZE AS SHOWN.		EMERGENCY GENERATOR
	FUSE		GROUND CONNECTION POINT
	INSULATED CASE CIRCUIT BREAKER		ELECTRONIC TRIP SETTING CONTROL (GROUND FAULT)
	INTEGRAL BREAKER AND STARTER UNIT, BREAKER AND FRAME SIZE AS SHOWN.		GROUND LOOP
	INTEGRAL SWITCH AND FUSE UNIT, FUSE AND FRAME SIZE AS SHOWN.		HIGH RESISTANCE GROUND FAULT SYSTEM
	LOAD BREAK ISOLATION SWITCH, VOLTAGE AND FRAME SIZE AS SHOWN.		LIGHTNING SURGE ARRESTER
	AUTOMATIC TRANSFER SWITCH WITH BY-PASS		LOAD BANK
	AUTOMATIC TRANSFER SWITCH WITHOUT BY-PASS		METERING SOCKET
	FIRE PUMP AUTOMATIC TRANSFER SWITCH (AND STARTER UNIT (BY OTHERS))		METERING CABINET
	MANUAL TRANSFER SWITCH OR DOUBLE THROW SWITCH		DIGITAL ELECTRONIC METER
			AMMETER

8 SINGLE LINE 1 OF 2
E010

[illegible]

9 SINGLE LINE 2 OF 2
E010

























SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	WALL MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R		WALL MOUNTED SIMPLEX RECEPTACLE 250V, 15 AMP, CSA 14-15R
	WALL MOUNTED ABOVE COUNTER DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R		WALL MOUNTED COMBINATION COMMUNICATION / DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R REFER TO CORRESPONDING DETAIL
	WALL MOUNTED DUPLEX RECEPTACLE 120V, 20 AMP, CSA 5-20R		FLOOR OR CEILING MOUNTED (AS SHOWN) COMBINATION COMMUNICATION / DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R REFER TO CORRESPONDING DETAIL
	WALL MOUNTED ABOVE COUNTER DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R, DEDICATED CIRCUIT		FLOOR POKE THROUGH COMBINATION COMMUNICATION / DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R REFER TO CORRESPONDING DETAIL
	WALL MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R, SPLIT CIRCUIT		WALL MOUNTED COMBINATION COMMUNICATION / DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R REFER TO CORRESPONDING DETAIL
	WALL MOUNTED DUPLEX GROUND FAULT RECEPTACLE 120V, 15 AMP, CSA 5-15R		FLOOR OR CEILING MOUNTED (AS SHOWN) COMBINATION COMMUNICATION / DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R REFER TO CORRESPONDING DETAIL
	WALL MOUNTED ABOVE COUNTER DUPLEX GROUND FAULT RECEPTACLE 120V, 15 AMP, CSA 5-15R		FLOOR POKE THROUGH COMBINATION COMMUNICATION / DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R REFER TO CORRESPONDING DETAIL
	WALL MOUNTED DUPLEX GROUND FAULT RECEPTACLE 120V, 20 AMP, CSA 5-20R		CEILING MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, 2 POLE, SPLIT CIRCUIT
	WALL MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R		CEILING MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, 2 POLE, SPLIT CIRCUIT
	WALL MOUNTED ABOVE COUNTER DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R		CEILING MOUNTED SIMPLEX RECEPTACLE 250V, 15 AMP, CSA 14-15R
	WALL MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, 2 POLE, SPLIT CIRCUIT		CEILING MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, 2 POLE, SPLIT CIRCUIT
	WALL MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, 2 POLE, SPLIT CIRCUIT		FLOOR MOUNTED DUPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R
	SPECIAL RECEPTACLE, TYPE AND DETAILS AS NOTED ON DRAWING		RACEWAY RECEPTACLE TYPE AS SPECIFIED ON DRAWING. SERVICES INDICATED
	WALL MOUNTED ABOVE COUNTER SIMPLEX RECEPTACLE 120V, 15 AMP, CSA 5-15R		SERVICES ONLY, TYPE AS SPECIFIED ON QUANTITY OF DEVICES INDICATED
	WALL MOUNTED SIMPLEX RECEPTACLE 250V, 20 AMP, CSA 5-20R		WALL MOUNTED RECEPTACLE C/W USB A&C LEVITON T8034-W
	WALL MOUNTED SIMPLEX RECEPTACLE 250V, 20 AMP, CSA 5-20R		

NOTE: NOT ALL SYMBOLS APPLY, REFER TO DRAWINGS

4 POWER LEGEND 1 OF 2
E010

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	FLUSH MOUNTED SINGLE TUB PANEL RATING AS NOTED ON SINGLE LINE PANEL SCHEDULE		CONTACTOR
	FLUSH MOUNTED DOUBLE TUB PANEL RATING AS NOTED ON SINGLE LINE PANEL SCHEDULE		GROUND ROD WITH INSPECTION PIT
	SURFACE MOUNTED SINGLE TUB PANEL RATING AS NOTED ON SINGLE LINE PANEL SCHEDULE		THERMOSTAT - 16mm (1/2") CONDUC TO ACCESSIBLE CEILING SPACE
	SURFACE MOUNTED DOUBLE TUB PANEL RATING AS NOTED ON SINGLE LINE PANEL SCHEDULE		JUNCTION BOX (SIZE SPECIFIED ON DRAWING)
	TRANSFORMER (SIZE NOTED ON SINGLE LINE DIAGRAM)		ELECTRIC UNIT HEATER
	DISCONNECT		ELECTRIC BASEBOARD HEATER "X" DENOTES TYPE. REFER TO BASEBOARD HEATER SCHEDULE
	COMBINATION MANUAL STARTER WITH INTEGRAL DISCONNECT		GROUND BAR
	COMBINATION STARTER WITH INTEGRAL DISCONNECT		HAND DRYER HAND WIRED CONNECTION
	DIRECT CONNECTION		METER
	600V DIRECT CONNECTION		RELAY
	DIRECT CONNECTION CW DISCONNECT		PULL BOX
	600V DIRECT CONNECTION CW DISCONNECT		GROUND BUS
	MOTOR AND DISCONNECT		DENOTES RECEPTACLE TYPE. REFER TO RECEPTACLE SCHEDULE
	MOTOR AND RELAY DISCONNECT		UTILITY METERING CABINET
	MOTOR AND COMBINATION STARTER WITH INTEGRAL DISCONNECT		DOOR BELL / CHIME
	VARIABLE FREQUENCY DRIVE AND LOAD SIDE WIRING OF CABLE, LINE AND VFD BY ELECTRICAL CONTRACTOR		CLOCK WALL MOUNTED
	VARIABLE FREQUENCY DRIVE AND LOAD SIDE WIRING OF CABLE, LINE AND VFD BY ELECTRICAL CONTRACTOR		CLOCK CEILING MOUNTED
	VARIABLE FREQUENCY DRIVE AND LOAD SIDE WIRING OF CABLE, LINE AND VFD BY ELECTRICAL CONTRACTOR		PUSH BUTTON
	VARIABLE FREQUENCY DRIVE AND LOAD SIDE WIRING OF CABLE, LINE AND VFD BY ELECTRICAL CONTRACTOR		MOTOR
	HARMONIC FILTER (SUPPLIED BY MECHANICAL CONTRACTOR UNLESS NOTED OTHERWISE) LINE AND LOAD SIDE WIRING OF HARMONIC FILTER BY ELECTRICAL CONTRACTOR		SOLAR PANEL

5 POWER LEGEND 2 OF 2
E010

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
ALARM INITIATING DEVICES			
	CEILING MOUNTED PHOTO-ELECTRIC SMOKE DETECTOR		AIR SAMPLING SYSTEM
	WALL MOUNTED PHOTO-ELECTRIC SMOKE DETECTOR		MANUAL STATION
	CEILING MOUNTED PHOTO-ELECTRIC SMOKE DETECTOR WITH RELAY BASE		BEAM SMOKE DETECTOR (TRANSMITTER)
	CEILING MOUNTED RATE-OF-RISE HEAT DETECTOR		BEAM SMOKE DETECTOR (RECEIVER)
	WALL MOUNTED RATE-OF-RISE HEAT DETECTOR		FLAME DETECTOR
	CEILING MOUNTED FIXED TEMPERATURE HEAT DETECTOR		
	WALL MOUNTED FIXED TEMPERATURE HEAT DETECTOR		
	DUCT TYPE PHOTO-ELECTRIC SMOKE DETECTOR		
	DUCT TYPE PHOTO-ELECTRIC SMOKE DETECTOR COMPLETE WITH HEATER		
	CEILING MOUNTED COMBINATION HEAT & SMOKE DETECTOR		
LOCAL ALARM DEVICES			
	LOCAL 120V SMOKE ALARM		LOCAL 120V COMBINATION SMOKE ALARM AND STROBE
	LOCAL 120V COMBINATION CARBON MONOXIDE AND SMOKE ALARM		LOCAL 120V COMBINATION CARBON MONOXIDE, SMOKE ALARM AND STROBE
	LOCAL 120V CARBON MONOXIDE ALARM		
SPRINKLER STANDPIPE DEVICES			
	LOW PRESSURE SUPERVISED SWITCH (SUPPLIED BY OTHERS)		ALARM DRY PIPE VALVE (SUPPLIED BY OTHERS)
	SPRINKLER SUPERVISED VALVE (SUPPLIED BY OTHERS)		
	ALARM FLOW SWITCH (SUPPLIED BY OTHERS)		
	ALARM PRESSURE SWITCH (SUPPLIED BY OTHERS)		
	ALARM CHECK VALVE (SUPPLIED BY OTHERS)		

NOTE: NOT ALL SYMBOLS APPLY. REFER TO DRAWINGS

6 FIRE ALARM LEGEND 1 OF 2
E010

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	DETAIL NUMBER DRAWING NUMBER		SECTION NUMBER DRAWING NUMBER
	REVISION NUMBER		REVISION BUBBLE
A	AMPS	MO	MOTOR OPERATED
AD	ACCESS DOOR	MOD	MOTOR OPERATED RAMMER
AF	ARC FAULT CIRCUIT INTERRUPTER	MW	MICROWAVE
AFI	AFTER FINISHED FLOOR	N	NEW
BBH	BASEBOARD HEATER	NC	NORMALLY CLOSED
BU	BATTERY UNIT	NC	NOT IN CONTRACT
C	CONDUIT	NL	NIGHT LIGHT
CD	CANDLE	NO	NORMALLY OPEN
CL	CEILING MOUNTED	OC	OVER COUNTER
CS	CHARGING STATION	OL	OBSTRUCTION LIGHT
CV	CONVENTIONAL STYLE DEVICE	P	PARALLEL LOUVE
D	DEDICATED	PL	PATIENT LIFT
DG	DEDICATED GROUND	R	RELOCATE
DHWT	DOMESTIC HOT WATER TANK	RA	RANGE
DNC	DEDICATED NEUTRAL + BOND	RE	REMOVE EXISTING CIRCUIT
DW	DISHWASHER	RH	RANGE HOOD
E	EXISTING	RIC	ROUGH IN AND CONNECT
EAF	EXHAUST FAN	RO	ROUGH IN ONLY
EM	EMERGENCY CIRCUIT	RR	REMOVE AND REINSTALL
EP	ELECTRICAL SUITE PANEL	SC	SEPARATE CIRCUIT
ER	EXISTING TO BE REMOVED	SF	SYSTEM FURNITURE
F	REFRIGERATOR	SP	SUITE ALARM PANEL
FF	FLOOR FEEB	SSP	SLAVE SUITE ALARM PANEL
FFH	FLOOR FLOOR HEATER	TYP	TYPICAL
FL	FLOOR MOUNTED	UC	UNDER CABINET MOUNTED
GFCI	GROUND FAULT CIRCUIT INTERRUPTER	U	UPS CIRCUIT
GFI	GROUND FAULT INTERRUPTER	UH	UNIT HATER
GRD	GROUND	UPS	UNINTERRUPTIBLE POWER SUPPLY
HK	HOLE KEEPING	V	VOLTS
HMT	HARMONIC MITIGATING TRANSFORMER	W	WATTS
ICE	ICE MACHINE	WG	WIRE GUARD
IG	IGATED GROUND	WAP	WIRELESS ACCESS POINT
JB	JUNCTION BOX	WF	WALL FEEB
KW	KILOWATTS	WP	WATERPROOF
LV	LOW VOLTAGE	X	EXPLOSION PROOF DEVICE + BACK BOX
		ZSCT	ZERO SEQUENCE CURRENT TRANSFORMER

NOTE: NOT ALL SYMBOLS APPLY. REFER TO DRAWINGS


1 GENERAL, SYMBOLS AND ABBREVIATIONS
E010

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	CEILING MOUNTED LINEAR LUMINAIRE. DIMENSIONS AS SHOWN. REFER TO SCHEDULE FOR TYPE		CEILING MOUNTED WALL WASHER LUMINAIRE. ILLUMINATION DIRECTION DENOTED BY MATCHED SIDE
	DENOTES FIXTURE ON EMERGENCY/NOT LIGHT CIRCUIT		CEILING MOUNTED TRACK LIGHTING CW NUMBER OF FIXTURES
	WALL MOUNTED LINEAR LUMINAIRE. DIMENSIONS AS SHOWN. REFER TO SCHEDULE FOR TYPE		WALL MOUNTED LUMINAIRE
	EXISTING LUMINAIRE TO BE REMOVED		PENDANT FIXTURE
	EXISTING LUMINAIRE TO REMAIN		CEILING MOUNTED LUMINAIRE
	CEILING MOUNTED LUMINAIRE WITH DIMMABLE HEADS. REFER TO SCHEDULE FOR TYPE AND NUMBER OF HEADS		FLOOR MOUNTED LUMINAIRE
	VERTICAL WALL MOUNTED FLUORESCENT LUMINAIRE		BOLLARD LUMINAIRE
	CONTINUOUS STRIP LIGHT. REFER TO SCHEDULE FOR FIXTURE TYPE		POLE MOUNTED LUMINAIRE. NUMBER OF HEADS SHOWN. REFER TO SCHEDULE FOR FIXTURE AND POLE TYPE
	RECESSED CEILING MOUNTED REMOTE ADJUSTABLE LUMINAIRE CONNECTED TO EMERGENCY LIGHTING BATTERY UNIT		EMERGENCY LIGHTING BATTERY UNIT CW NUMBER OF HEADS SHOWN. COMPLETELY W/ DIRECT CONNECTION OR RECEPTACLE
	WALL MOUNTED EMERGENCY SINGLE REMOTE HEAD		EMERGENCY LIGHTING BATTERY UNIT
	CEILING MOUNTED EMERGENCY DOUBLE REMOTE HEAD		EMERGENCY LIGHTING BATTERY + EXT LIGHT COMBINATION UNIT CW NUMBER OF HEADS SHOWN
	CEILING MOUNTED EMERGENCY SINGLE REMOTE HEAD		EXIT LIGHT CEILING MOUNTED CW FACES AND ARROWS AS INDICATED
	CEILING MOUNTED EMERGENCY DOUBLE REMOTE HEAD		EXIT LIGHT WALL MOUNTED CW FACES AND ARROWS AS INDICATED

2 LIGHTING LEGEND 1 OF 2
E010

[illegible]

3 LIGHTING LEGEND 2 OF 2
E010




REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR F&S REVIEW
4	2024-12-23	ISSUED FOR F&S REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



Smith + Andersen
1100 • 100 Sheppard Ave East, Toronto ON, M2N 6N5
t 416-487-8151 smithandandersen.com

ENFORM
architects

ENFORM Architects Inc.
128A Sterling Road, Suite 302B
Toronto, Ontario, Canada M6R 2B7
T: 647-948-7523
www.enformarchitects.com

SEAL:	
OWNER:	
 <div style="display: inline-block; vertical-align: middle;"> UNIVERSITY OF TORONTO </div>	

PROJECT :
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER


214 COLLEGE ST,
TORONTO, ON M5T 3A1

LEGENDS - ELECTRICAL


PROJECT NUMBER : 21590.003		
DRAWING SCALE : NTS.		
DRAWN BY : Author	CHECKED BY : Checker	DATE: Issue Date
SHEET NO. _____		REV. _____

E010	6
-------------	----------

KEY PLAN:




REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-01	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



NOTES:

- (N-1) PROVIDE CONNECTOR, C/W NYLON BUSHINGS FOR CONDUIT TERMINATIONS WITHIN ACCESSIBLE CEILING SPACE.
(N-2) PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT.
(N-3) COVER PLATES BY DIVISION 26.


5
E01 POWER AND COMMUNICATION OUTLETS
SCALE: N.T.S.



NOTES:

- (N-1) PROVIDE CONNECTOR, C/W NYLON BUSHINGS FOR CONDUIT TERMINATIONS WITHIN ACCESSIBLE CEILING SPACE.
(N-2) PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT.
(N-3) COVER PLATES BY DIVISION 26.


2
E01 POWER AND COMMUNICATION OUTLETS
SCALE: N.T.S.




NOTES:

- (N-1) PROVIDE CONNECTOR, C/W NYLON BUSHINGS FOR CONDUIT TERMINATIONS WITHIN ACCESSIBLE CEILING SPACE.
(N-2) PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT.
(N-3) COVER PLATES BY DIVISION 26.

1
E01 POWER AND COMMUNICATION OUTLETS
SCALE: N.T.S.




6
E01 TRANSFORMER INSTALLATION DETAIL
SCALE: N.T.S.



NOTES:

- (N-1) MINIMUM SIZE CONDUITS SHALL BE 21mmC (3/4") UNLESS OTHERWISE NOTED.
(N-2) ALL PUSH BUTTONS ARE TO BE MOUNTED AT 105mm ABOVE FINISHED FLOOR AND ARE TO BE OPERABLE USING A CLOSED FIST.
(N-3) ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL COMBINATION EMERGENCY PUSH BUTTON AND VISUAL SIGNAL DEVICE INSIDE OF WASHROOM. INTERNAL VISUAL DEVICE TO ACTIVATE WHEN EMERGENCY BUTTON IS PRESSED. EMERGENCY BUTTON TO BE MUSHROOM STYLE AND LATCHING TYPE, SUCH THAT VISUAL INDICATOR WILL REMAIN ACTIVATED ONCE PRESSED. MUSHROOM STYLE BUTTON TO BE TWIST-TO-RELEASE TYPE TO ALLOW EASE OF TURNING OFF. VISUAL INDICATOR AFTER WASHROOM OCCUPANT HAS BEEN ASSISTED. PUSH BUTTON TO ALSO ILLUMINATE SPECIAL WORDING SIGNAGE AND ACTIVATE PIEZO CHIME. BUILT AND LOCATED OUTSIDE OF THE WASHROOM. PUSH BUTTON & VISUAL ALARM COMPONENTS TO BE MOUNTED ON STAINLESS STEEL FACEPLATE.
MOUNT COMBINATION DEVICE SUCH THAT THE CENTRE OF THE PUSHBUTTON IS LOCATED AT 105mm ABOVE FINISHED FLOOR. INTERNAL VISUAL DEVICE TO BE LIT BY AN LED SOURCE. COMBINATION DEVICE TO BE 24 VOLT DC STYLE FOR EASY INTEGRATION WITH WASHROOM DOOR ELECTRIC STRIKE. WASHROOM DOOR ELECTRIC STRIKE TO BE RELEASED WHEN EMERGENCY BUTTON IS PRESSED TO ALLOW MANUAL ACCESS TO WASHROOM TO PROVIDE ASSISTANCE. DOOR OPERATOR IS NOT TO OPEN DOOR WHEN EMERGENCY BUTTON IS PRESSED.
SUBMIT SHOP DRAWINGS FOR ARCHITECT AND CONSULTANT REVIEW PRIOR TO MANUFACTURING/RELEASE.
(N-4) ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL PIEZO CHIME OUTSIDE OUTSIDE OF THE WASHROOM. WHEN THE EMERGENCY BUTTON IS PRESSED, THE PIEZO CHIME IS TO SOUND. CHIME OUTSIDE OF WASHROOM TO HAVE SOUND PRESSURE LEVEL OF 82 DBA AT 1 METERS. CHIME TO BE 24 VOLT DC TYPE. SUBMIT SHOP DRAWINGS OF PIEZO CHIME FOR ARCHITECT AND CONSULTANT REVIEW PRIOR TO MANUFACTURING/RELEASE.
(N-5) ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL ASSISTANCE REQUIRED COMPLETE WITH WHEELCHAIR GRAPHIC SPECIAL WORDING SIGNAGE OUTSIDE OF THE WASHROOM. WHEN THE EMERGENCY BUTTON IS PRESSED, THE SIGN IS TO ILLUMINATE. SIGN TO BE 24 VOLT DC TYPE. SUBMIT SHOP DRAWINGS FOR ARCHITECT AND ELECTRICAL CONSULTANT REVIEW PRIOR TO MANUFACTURING/RELEASE. ILLUMINATED SIGN TO BE EMERGENCY LIGHT OR APPROVED EQUAL.
(N-6) ELECTRICAL CONTRACTOR TO PROVIDE ALL CONDUIT, WIRING, POWER SUPPLIES, AND CONNECTIONS DETAILLED ABOVE FOR ALL UNIVERSAL WASHROOMS. ALL WIRING TO BE INSTALLED IN CONDUIT.
(N-7) ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL A LAMACOD SIGN ABOVE THE EMERGENCY BUTTON THAT READS "IN THE EVENT OF AN EMERGENCY PUSH EMERGENCY BUTTON AND AUDIBLE AND VISUAL SIGNAL WILL ACTIVATE". LETTERS ON LAMACOD MUST BE AT LEAST 25mm HIGH WITH A 5mm STROKE. SUBMIT SHOP DRAWING FOR ARCHITECT AND CONSULTANT REVIEW PRIOR TO MANUFACTURING AND RELEASE.
(N-8) ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL 24 VOLT DC POWER SUPPLY IN A SEPARATE JUNCTION BOX WITH SUFFICIENT CAPACITY TO POWER ALL EMERGENCY CALL SYSTEM COMPONENTS INCLUDING ALL AUDIBLE AND VISUAL INDICATORS AS WELL AS DOOR ELECTRIC STRIKE RELEASE. ADDITIONALLY, POWER SUPPLY TO HAVE 500% SPARE CAPACITY FOR FUTURE USE. POWER SUPPLY INPUT TO BE 120V.
(N-9) REFER TO INTERIOR DESIGNER'S DRAWINGS FOR EXACT DEVICE LOCATIONS.
(N-10) NEW 20A, GFI RECEPTACLE FOR ADULT CHANGE TABLE. PROVIDE CIRCUIT FROM NEAREST AVAILABLE BASE-BUILDING PANEL.


3
E01 TYPICAL UNIVERSAL WASHROOM SCHEMATIC AND FLOOR PLAN
SCALE: 1/2"=1'-0"



NOTES:

- (N-1) PROVIDE RECEPTACLE C/W WEATHERPROOF WHILE-IN-USE COVER. RECEPTACLE TO BE MOUNTED ON INDEPENDENTLY SUPPORTED UNISTRUT STANDOFF AS SHOWN ABOVE. PROVIDE LIQUID TIGHT FLEXIBLE CONDUIT WHEN CONDUIT RUN IS OUTDOORS.
(N-2) ALL EQUIPMENT AND COMPONENTS TO BE SUPPLIED AND INSTALLED BY THE ELECTRICAL CONTRACTOR UNLESS OTHERWISE NOTED.

7
E01 ROOFTOP MAINTENANCE RECEPTACLE
N.T.S.



NOTES:

- (N-1) PROVIDE ROUGH-IN FOR PUSH PADDLES, DOOR OPENER, ELECTRIC STRIKE, AND JUNCTION BOX COMPLETE WITH EMT AND BLANK COVERPLATES. EQUIPMENT TO BE SUPPLIED AND INSTALLED BY OTHERS.
(N-2) 3/4" CONDUIT
(N-3) REFER TO ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS OF PUSH BUTTONS.
(N-4) ALL DEVICES ARE BY OTHERS.
(N-5) WIRING FOR ALL DEVICES SUPPLIED BY OTHERS, INSTALLED BY THIS CONTRACTOR.
(N-6) ASSISTANCE REQUIRED SIGN
(N-7) REFER TO ARCHITECTURAL DRAWING FOR FINAL DEVICE LOCATION.

4
E01 TYPICAL UNIVERSAL WASHROOM DOOR DETAIL
SCALE: N.T.S.



SEAL:

OWNER:



PROJECT:
**HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER**

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
**STANDARD DETAILS -
ELECTRICAL**

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100

DRAWN BY: Author CHECKED BY: Checker DATE: Issue Date

SHEET NO.: **E020** REV: **6**

PROJECT NAME: UoT Koffler											
Project number: 21590.003.E.001											
Date: 2024.11.15											
FIRE ALARM ZONE SCHEDULE						FIRE ALARM ZONE SCHEDULE					
Zone No.			Annunciator Label	Description/Note		Zone No.			Annunciator Label	Description/Note	
Alarm Zones						Alarm Zones					
1			STATION BASEMENT NORTH	EXISTING		61			SPRINKLER VALVE MALL	EXISTING	
2			STATION BASEMENT SOUTH	EXISTING		62			SPRINKLER VALVE 1ST FLOOR SOUTH	EXISTING	
3			1ST FLOOR NORTH	EXISTING		63			SPRINKLER VALVE MEZZANINE NORTH	EXISTING	
4			1ST FLOOR SOUTH	EXISTING		64			SPRINKLER VALVE 2ND FLOOR NORTH	EXISTING	
5			MEZZANINE NORTH	EXISTING		65			SPRINKLER VALVE 2ND FLOOR SOUTH	EXISTING	
6			2ND FLOOR NORTH	EXISTING		66			SPRINKLER VALVE 3RD FLOOR NORTH	EXISTING	
7			2ND FLOOR SOUTH	EXISTING		67			SPRINKLER VALVE 3RD FLOOR SOUTH	EXISTING	
8			3RD FLOOR NORTH	EXISTING		68			SPRINKLER VALVE PENTHOUSE 1 & 2	EXISTING	
9			3RD FLOOR NORTH	EXISTING		69			SPRINKLER VALVE PENTHOUSE 3	EXISTING	
10			PENTHOUSE 1 & 2 & CATWALK	EXISTING		70			STANDPIPE VALVE RISER 1	EXISTING	
11			PENTHOUSE 3	EXISTING		71			STANDPIPE VALVE RISER 2	EXISTING	
12			SPRINKLER FLOW BASEMENT NORTH	EXISTING		72			STANDPIPE VALVE RISER 3	EXISTING	
13			SPRINKLER FLOW BASEMENT SOUTH	EXISTING		73			STANDPIPE VALVE RISER 4	EXISTING	
14			SPRINKLER FLOW 1ST FLOOR NORTH	EXISTING		74			STANDPIPE VALVE BOOSTER PUMP INLET	EXISTING	
15			SPRINKLER FLOW 1ST FLOOR SOUTH	EXISTING		75			STANDPIPE VALVE BOOSTER PUMP OUTLET	EXISTING	
16			SPRINKLER FLOW MEZZANINE NORTH	EXISTING		76			DOMESTIC & STANDPIPE MAIN FEED	EXISTING	
17			SPRINKLER FLOW 2ND FLOOR NORTH	EXISTING		77			SPRINKLER LOW PRESSURE MAIN SOUTH	EXISTING	
18			SPRINKLER FLOW 2ND FLOOR SOUTH	EXISTING		78			SPRINKLER LOW PRESSURE MAIN NORTH	EXISTING	
19			SPRINKLER FLOW 3RD FLOOR NORTH	EXISTING		79			STANDPIPE LOW PRESSURE BOOSTER PUMP SUCTION	EXISTING	
20			SPRINKLER FLOW 3RD FLOOR SOUTH	EXISTING		80			STANDPIPE LOW PRESSURE BOOSTER PUMP DISCHARGE	EXISTING	
21			SPRINKLER FLOW PENTHOUSE 1 & 2	EXISTING		81			STANDPIPE POWER LOSS EXCESS PRESSURE PUMP	EXISTING	
22			SPRINKLER FLOW PENTHOUSE 3 NORTH	EXISTING		82			SPRINKLER VALVE GRND FLR KOFFLER WINDOW	EXISTING	
23			SPRINKLER FLOW ATRIUM MALL	EXISTING		83			SPRINKLER VALVE 2ND FLR KOFFLER WINDOW	EXISTING	
24			SMOKE DETECTOR SOUTH WEST STAIR	EXISTING		84			SPRINKLER VALVE 3RD FLR KOFFLER WINDOW	EXISTING	
25			SMOKE DETECTOR CENTRE WEST STAIR	EXISTING		85			MAIN WATER INCOMING STANDPIPE	EXISTING	
26			SMOKE DETECTOR NORTH WEST STAIR	EXISTING		86			STANDPIPE DOUBLE CHECK VALVE INLET	EXISTING	
27			SMOKE DETECTOR SOUTH EAST STAIR	EXISTING		87			STANDPIPE DOUBLE CHECK VALVE OUTLET	EXISTING	
28			SMOKE DETECTOR NORTH EAST STAIR	EXISTING		88			STANDPIPE DOUBLE CHECK VALVE INLET	EXISTING	
29				EXISTING		89			STANDPIPE DOUBLE CHECK VALVE OUTLET	EXISTING	
30			DUCT SMOKE DETECTOR (SD-1) - R/F-2	EXISTING		90			VESDA SYSTEM TROUBLE PANEL IN ROOM #320	EXISTING	
31			DUCT SMOKE DETECTOR (SD-2) - R/F-4	EXISTING		91			BAHEN ALARM	EXISTING	
32			DUCT SMOKE DETECTOR (SD-3) - R/F-6	EXISTING		92	X		FA21 - BASEMENT NEW ELEVATOR PIT/SHAFT	DEVICE	
33			DUCT SMOKE DETECTOR (SD-4) - R/F-8	EXISTING		93	X		FA22 - 3F FIRE SHUTTERS	DEVICE	
34			DUCT SMOKE DETECTOR (SD-5) - R/F-5	EXISTING		94	X		FA23 - GND FLR KITCHEN HOOD SUPPRESSION SYSTEM	DEVICE	
35			DUCT SMOKE DETECTOR (SD-6) - R/F-12	EXISTING		95	X		FA24 - GRD FLOOR IT ROOM #122	DEVICE	
36			DUCT SMOKE DETECTOR (SD-7) - R/F-14	EXISTING		96	X		FA25 - GND FLOOR ELECTRICAL ROOM #107B	DEVICE	
37			HEAT DETECTOR ELEVATOR #1 PIT/SHAFT/MACH	EXISTING		97	X		FA26 - GND FLOOR ELECTRICAL CLOSET	DEVICE	
38			HEAT DETECTOR ELEVATOR #2 PIT/SHAFT/MACH	EXISTING		98	X		FA27 - 2ND FLOOR ELECTRICAL CLOSET #231B	DEVICE	
39			HEAT DETECTOR ELEVATOR #3 PIT/SHAFT/MACH	EXISTING		99	X		FA28 - 2ND FLOOR IT CLOSET #231B	DEVICE	
40			SPRINKLER FLOW GRND FLOOR BAHEN	EXISTING		100	X		FA29 - 2ND FLOOR IT CLOSET #238	DEVICE	
41			SPRINKLER FLOW GRND FLOOR KOFFLER WINDOW	EXISTING		101	X		FA210 - 2ND FLOOR ELECTRICAL CLOSET #274	DEVICE	
42			SPRINKLER FLOW 2ND FLR KOFFLER WINDOW	EXISTING		102	X		FA211 - 2ND FLOOR IT ROOM #277	DEVICE	
43			SPRINKLER FLOW 3RD FLR KOFFLER WINDOW	EXISTING		103	X		FA212 - 2ND FLOOR ELECTRICAL CLOSET #276	DEVICE	
44			VESDA SYSTEM ATRIUM SMOKE DETECTOR PANEL IN ROOM #320	EXISTING		104	X		FA211 - 3RD FLOOR ELECTRICAL CLOSET	DEVICE	
45			BASEMENT SOUTH ELEVATOR 1 MACHINE ROOM	EXISTING		105	X		FA214 - 3RD FLOOR SOUTH ELEVATOR LOBBY (EX)	DEVICE	
46			1ST FLOOR NORTH ELEVATOR 2 MACHINE ROOM	EXISTING		106	X		FA215 - 3RD FLOOR SOUTH MECHANICAL ROOM	DEVICE	
47			PENTHOUSE 3 ELEVATOR 3 MACHINE ROOM	EXISTING		107	X		FA216 - 3RD FLOOR ELEC. CLOSET	DEVICE	
48			DUCT SMOKE DETECTOR (SD-8) - AHS-1	EXISTING		108	X		FA217 - 3RD FLOOR ELEVATOR MACHINE ROOM	DEVICE	
49			DUCT SMOKE DETECTOR (SD-9) - AHS-2	EXISTING		109	X		FA218 - 3RD FLOOR ELECTRICAL ROOM #372	DEVICE	
50			DUCT SMOKE DETECTOR (SD-10) - AHS-3	EXISTING		110	X		FA219 - SUPERVISORY 2F FIRE HOSE CABINET	DEVICE	
51			DUCT SMOKE DETECTOR (SD-11) - AHS-5	EXISTING		111	X		FA220 - 3RD FLOOR IT CLOSET #399C	DEVICE	
52			DUCT SMOKE DETECTOR (SD-12) - AHS-6	EXISTING		112	X		FA221 - SUPERVISORY 2F FIRE HOSE CABINET	DEVICE	
53			DUCT SMOKE DETECTOR (SD-13) - AHS-7	EXISTING		113					
54			DUCT SMOKE DETECTOR (SD-5) - AHS-5	EXISTING		114					
55			SPRINKLER VALVE MAIN INCOMING	EXISTING		115					
56			SPRINKLER VALVE MAIN NORTH	EXISTING		116					
57			SPRINKLER VALVE MAIN NORTH	EXISTING		117					
58			SPRINKLER VALVE BASEMENT SOUTH	EXISTING		118					
59			SPRINKLER VALVE BASEMENT NORTH	EXISTING		119					
60			SPRINKLER VALVE 1ST FLOOR NORTH	EXISTING		120					
Auxiliary Control/Monitoring points											
1		X	ELEV. CTRL FA MACHINE ROOM STATUS	Aux. Contact (Control)		7		X	FIRE SHUTTER RELEASE	Aux. Contact (Control)	
2		X	ELEV. CTRL FA RECALL FLOOR STATUS	Aux. Contact (Control)		8					
3		X	ELEV. CTRL FA ALT RECALL FLOOR STATUS	Aux. Contact (Control)		9					
4		X	ELEV. CTRL FA TOP OF SHAFT STATUS	Aux. Contact (Control)		10					
5		X	ELEV. CTRL FA PIT DETECTOR STATUS	Aux. Contact (Control)		11					
6		X	ELEVATOR RECALL	Aux. Contact (Control)		12					
Notes:											
1. All existing zones are to remain denoted as light/greyed out zones											
2. Submit fire alarm zones graphic showing existing and new zones for review and approval.											
3. Provide typed, updated zone schedules on main fire alarm control panel as well as annunciator panels as required.											
4. New zones are denoted in bold.											

6


EST

FIRE ALARM ZONE SCHEDULE

SCALE: NTS


6
E021

FIRE ALARM ZONE SCHEDULE
SCALE: NTS




4
E021

GROUNDING BUS BAR
SCALE: NTS




5
E021

FURNITURE SYSTEM CONNECTION - WIREMOLD
SCALE: NTS




3
E021

QUAD POKE-THROUGH POWER/DATA/AUDIO VISUAL OUTLET
SCALE: NTS




1
E021

CONNECTRAC RACEWAY SYSTEM DETAIL
SCALE: NTS




2
E021

TYPICAL TWO COMPARTMENT WIREMOLD RACEWAY
SCALE: NTS



3
E021

QUAD POKE-THROUGH POWER/DATA/AUDIO VISUAL OUTLET
SCALE: NTS



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID

Smith + Andersen
1100 - 109 Sheppard Ave East, Toronto, ON, M2N 6N6
416-467-8151 smithandandersen.com

ENFORM architects
ENFORM Architects Inc.
1284 Sheppard Road, Suite 302B
Toronto, Ontario, Canada M8R 2B7
416-546-7523
www.enformarchitects.com

SEAL:

UNIVERSITY OF TORONTO

PROJECT:
HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
STANDARD DETAILS - ELECTRICAL

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100

DRAWN BY:
Author


CHECKED BY:
Checker

DATE:
Issue Date

SHEET NO.:
E021

REV:
6

LIGHTING CONTROL DEVICE SCHEDULE		
TYPE	DESCRIPTION	MANUFACTURER/CATALOGUE NO.
OS	ENCELIUM WIRED OCCUPANCY SENSOR	50356-EN-SCPH-1500-GB2
OS HB	ENCELIUM WIRED HIGH BAY OCCUPANCY SENSOR	50357-EN-SCPH-HB-GB2
D	ENCELIUM 3 SCENE WALL STATION	ENCELIUM EN-W5-SC3-GB2-WH
D02	ENCELIUM 5 SCENE WALL STATION	ENCELIUM EN-W5-SC5-GB2-WH
D03	ENCELIUM WALL DIMMER	ENCELIUM EN-W5-4B-GB2-WH
D04	ENCELIUM WALL SWITCH (ON/OFF ONLY)	ENCELIUM EN-W5-2B-GB2-WH
D05	ENCELIUM TOUCHSCREEN	ENCELIUM KX4
OS	WALL MOUNTED 0-10V DIMMER & OCCUPANCY SENSOR	WATTSTOPPER DW-311 CW ENCELUM SENSOR INTERFACE MODULE
WM	WIRED MANAGER	EN-M-GB2-X (X: EN-ECU-G4-PD0 (EXTEND)
ALC	AREA LIGHTING CONTROLLER	ENCELIUM EN-ALC-1R10V-GB2-BK
LCM	LIGHTING CONTROL MODULE	ENCELIUM EN-LCM-1R10V-GB2-BK



GENERAL NOTE:


- ENCELIUM LIGHTING CONTROL SYSTEM IS A LONG LEAD ITEM. THE EXPECTED DELIVERY TIME CAN VARY BETWEEN 3 TO 6 MONTHS. CONTRACTOR IS ADVISED TO REVIEW THE DRAWINGS AND PLACE PURCHASE ORDER AS SOON AS POSSIBLE AFTER AWARDING THE CONTRACT. IN ORDER TO AVOID ANY DELAYS TO PROJECT SCHEDULE.
- REFER TO ELECTRICAL SPECIFICATION AND ALLOW FOR ADDITIONAL VISITS OF LIGHTING CONTROLS SPECIALIST AS REQUIRED. INCLUDE ALL ASSOCIATED COST IN TENDER PRICE AS REQUIRED.

LIGHTING CONTROL NOTES:

- EXACT LOCATION OF DEVICES TO BE CONFIRMED ON SITE.
- PROVIDE ENGRAVING KIT FOR ALL WALL BUTTONS, AS REQUIRED.
- DEVICES IN EACH ROOM SHALL OPERATE WITH OPEN TOPOLOGY AND CAN BE REARRANGED.
- PROVIDE STAINLESS STEEL COVER PLATE FOR WALL STATIONS.
- ALL CONTROL DEVICES TO BE INSTALLED WITHIN BACKBOXES AS REQUIRED.
- ALL LOW VOLTAGE AND CONTROL WIRING SHALL BE INSTALLED INSIDE EMT CONDUITS.
- CONTRACTOR MUST ADHERE TO ENCELIUM DRAWINGS. ANY MODIFICATIONS TO ENCELIUM DRAWINGS REQUIRE FACTORY APPROVAL.
- SENSORS MUST BE INSTALLED AS PER INDUSTRY STANDARD. REFER TO MANUFACTURER INSTRUCTION SHEET INCLUDED WITH SENSOR HARDWARE. - ALL SENSORS MUST BE MOUNTED AT LEAST 6 FEET AWAY FROM AIR VENTS & HEAT EXCHANGERS.
- UNLESS OTHERWISE NOTED, ALL SENSORS WILL OPERATE AUTO ON, AUTO OFF WITH A TIMEOUT OF 11 MINUTES.
- UNLESS OTHERWISE NOTED, ALL ENCELIUM WIRED MANAGERS SHOULD BE CONNECTED TO NORMAL POWER.
- COORDINATE WITH ENCELIUM TECHNICIAN TO ASSIGN SWITCHES TO THE RESPECTIVE FUTURE GROUPING, AS INDICATED ON LIGHTING ZONE LAYOUTS.
- ENCELIUM WIRED MANAGER (M), SYSTEM SUPPORT UNIT (SSU) AND WIRELESS MANAGER (WM) IS TO BE CONNECTED TO FAS NETWORK. ONE IP ADDRESS PER DEVICE MUST BE PROVIDED TO ENCELIUM PRIOR TO SYSTEM START UP.
- NETWORK RUNS MUST NOT EXCEED 100M (328FT.). ANY MODIFICATIONS TO ENCELIUM DRAWINGS REQUIRE FACTORY APPROVAL.
- REFER TO THE ENCELIUM CONTRACTOR'S INSTALLATION GUIDE FOR SYSTEM INFORMATION, CUT SHEETS, AND WIRING DIAGRAMS.
- SYSTEM NEEDS TO BE TESTED PRIOR TO REQUESTING SYSTEM STARTUP SERVICES. PLEASE REFER TO ENCELIUM CONTRACTOR MANUAL FOR TESTING PROCEDURE USING GREENBUS II TESTER AND/OR EEM G4 INSTALLATION MODE.
- END USER NETWORK ACCESS TO THE ENCELIUM SERVER (BSU) MUST BE ARRANGED PRIOR TO SYSTEM TRAINING.
- ENCELIUM PHASE CUT DRAWING MODULE (PCDM) HAS A MAXIMUM OUTPUT RATING OF: 120 VAC, 450W, 3.8A MAX.
- USE MINIMUM 3/4" CONDUIT FOR GREENBUS CABLEING.
- ALLOW FOR THE COST TO PROVIDE POE INJECTORS AS REQUIRED.
- ALLOW FOR SYSTEM INTEGRATION TO IAT ENCELIUM SERVER (INCLUDING BUT NOT LIMITED TO GRAPHIC SET UP, DATA COLLECTION, ETC.)

PARTITION SENSORS NOTES:

- THE PARTITION SENSOR MUST PROVIDE A HIGH SIGNAL WHEN AT CLOSED STATE AND THE ROOMS SHOULD ACT/OPERATES SEPARATELY.
- THE PARTITION SENSOR MUST PROVIDE A LOW SIGNAL WHEN AT OPEN STATE AND THE ROOMS SHOULD ACT/OPERATES COMBINED.



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%.
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID




SEAL :



PROJECT :
HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1
SHEET CONTENTS :
RISER DIAGRAM


PROJECT NUMBER : 21590.003		
DRAWING SCALE : 1 : 100		
DRAWN BY : Author	CHECKED BY : Checker	DATE : Issue Date
SHEET NO : E024	REV : 6	




3 FLOOR 3 - LIGHTING CONTROL KEYPLAN
E025 1:200



2 FLOOR 2 - LIGHTING CONTROL KEYPLAN
E025 1:200




1 FLOOR 1 - LIGHTING CONTROL KEYPLAN
E025 1:200



2 FLOOR 2 - LIGHTING CONTROL KEYPLAN
E025 1:200

KEY PLAN:



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:

OWNER:



PROJECT:
**HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER**

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LIGHTING CONTROL LAYOUT

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 200

DRAWN BY: CHECKED BY: DATE:
Author Checker Issue Date

SHEET NO.: REV: 6


E025

UNIT PRICE

DEMO DEMOLISH EXISTING CONDUIT BACK TO SOURCE AND PROVIDE NEW CONDUIT WITH SIZING AS SHOWN

CODED NOTES

CONF CONFIRM LOCATION OF EQUIPMENT WITH GC PRIOR TO ROUGH-IN



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR F&S REVIEW
4	2024-12-23	ISSUED FOR F&S REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID

ENFORM
architects

ENFORM Architects Inc.
128A Sterling Road, Suite 302B
Toronto, Ontario, Canada M6R 2B7
t: 647-948-7523
www.enformarchitects.com

PROJECT :
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SINGLE LINE DIAGRAM

PROJECT NUMBER :	21590.003
DRAWING SCALE :	

1 : 100		
DRAWN BY : Author	CHECKED BY : Checker	DATE: Issue Date

SHEET NO :	REV :
E026	6



UNIVERSITY OF TORONTO											
143-NDP-02-06-BA											
BLDG #:	143	PANEL TAG	DATE MODIFIED: 2025-02-13								
CONNECTED LOAD (W)	DEMAND FACTOR	TOTAL DEMAND	DESCRIPTION (Item, Room Number(s)):			BKR (A)	CT	CT	BKR (A)	DESCRIPTION (Item, Room Number(s)):	CONNECTED LOAD (W)
25000	100.00	2500000	TRANSFORMER 143-NTX-02-06-BA			90	1	A	2	20	SPACE
25000	100.00	2500000				↓	3	B	4	↓	0
25000	100.00	2500000				3P	5	B	6	3P	0
25000	100.00	2500000	TRANSFORMER 143-NTX-02-06-BC			90	7	A	8	20	SPACE
25000	100.00	2500000				↓	9	B	10	↓	0
25000	100.00	2500000				3P	11	B	12	3P	0
25000	100.00	2500000	TRANSFORMER 143-NTX-02-06-BB			90	13	A	14		SPACE
25000	100.00	2500000				↓	15	B	16		SPACE
25000	100.00	2500000				3P	17	B	18		SPACE
2700	100.00	270000	TRANSFORMER 143-NTX-02-06-BB			20	19	A	20		SPACE
2700	100.00	270000				↓	21	B	22		SPACE
2700	100.00	270000				3P	23	B	24		SPACE
0		0	SPARE			90	25	A	26		SPACE
0		0				↓	27	B	28		SPACE
0		0				3P	29	B	30		SPACE
0		0	SPARE			90	31	A	32		SPACE
0		0				↓	33	B	34		SPACE
0		0				3P	35	B	36		SPACE
0		0	SPARE			90	37	A	38		SPACE
0		0				↓	39	B	40		SPACE
0		0				3P	41	B	42		SPACE
			BLDG #:	143	FLOOR:	2	ROOM:	278	NEW TAG:	N/A	
			RATINGS:	400A	120/208V	3 PHASE	4 WIRE	S.C.:	10		
			FED. FROM:	PANEL TAG: EXISTING PP-MB	BLDG #:	143	ROOM #:	8013	BREAKER SIZE:	400A/3P	FEEDER SIZE: 3 000 KCMIL + #2 AWG IN 3" C
143-NDP-02-06-BA.xlsx											

1 E033

PANEL LP-EMB
SCALE: NTS

UNIVERSITY OF TORONTO											
143-NDP-03-02-BA											
BLDG #:	143	PANEL TAG	DATE MODIFIED: 2025-02-13								
CONNECTED LOAD (W)	DEMAND FACTOR	TOTAL DEMAND	DESCRIPTION (Item, Room Number(s)):			BKR (A)	CT	CT	BKR (A)	DESCRIPTION (Item, Room Number(s)):	CONNECTED LOAD (W)
760	1.00	760	143-NRP-03-02-BD			100	1	A	2	100	SPARE
760	1.00	760				↓	3	B	4	↓	0
760	1.00	760				3P	5	B	6	3P	0
610	1.00	610	143-NRP-03-02-BA			100	7	A	8	100	SPARE
610	1.00	610				↓	9	B	10	↓	0
610	1.00	610				3P	11	B	12	3P	0
674	1.00	674	143-NLP-03-02-BA			100	13	A	14		SPACE
674	1.00	674				↓	15	B	16		SPACE
674	1.00	674				3P	17	B	18		SPACE
625	1.00	625	143-NLP-03-02-BD			100	19	A	20		SPACE
625	1.00	625				↓	21	B	22		SPACE
625	1.00	625				3P	23	B	24		SPACE
2970	1.00	2970	143-NRP-03-02-BD			100	25	A	26		SPACE
2970	1.00	2970				↓	27	B	28		SPACE
2970	1.00	2970				3P	29	B	30		SPACE
0		0	SPARE			100	31	A	32		SPACE
0		0				↓	33	B	34		SPACE
0		0				3P	35	B	36		SPACE
0		0	SPARE			100	37	A	38		SPACE
0		0				↓	39	B	40		SPACE
0		0				3P	41	B	42		SPACE
			BLDG #:	143	FLOOR:	3	ROOM:	325	NEW TAG:	N/A	
			RATINGS:	225A	120/208V	3 PHASE	4 WIRE	S.C.:	10		
			FED. FROM:	PANEL TAG: EXISTING PP-SP	BLDG #:	143	ROOM #:	8013	BREAKER SIZE:	200A/3P	FEEDER SIZE: 4 #12 AWG + #4 AWG IN 3" C
143-NDP-03-02-BA.xlsx											

1 E033

PANEL LP-EMB
SCALE: NTS



UNIVERSITY OF TORONTO											
143-NDP-02-02-BA											
BLDG #:	143	PANEL TAG	DATE MODIFIED: 2025-03-13								
CONNECTED LOAD (W)	DEMAND FACTOR	TOTAL DEMAND	DESCRIPTION (Item, Room Number(s)):			BKR (A)	CT	CT	BKR (A)	DESCRIPTION (Item, Room Number(s)):	CONNECTED LOAD (W)
0		0	PANEL 143-NRP-02-02-BA, 231B			125	1	A	2	125	ELEVATOR MOTOR
0		0				↓	3	B	4	↓	0
0		0				3P	5	B	6	3P	0
0		0	PANEL 143-NRP-02-02-BC, 280			125	7	A	8		SPACE
0		0				↓	9	B	10		SPACE
0		0				3P	11	B	12		SPACE
0		0	PANEL 143-NRP-02-02-BA, 231D			125	13	A	14		SPACE
0		0				↓	15	B	16		SPACE
0		0				3P	17	B	18		SPACE
0		0	SPARE			125	19	A	20		SPACE
0		0				↓	21	B	22		SPACE
0		0				3P	23	B	24		SPACE
0		0	SPARE			125	25	A	26		SPACE
0		0				↓	27	B	28		SPACE
0		0				3P	29	B	30		SPACE
0		0	SPARE			125	31	A	32		SPACE
0		0				↓	33	B	34		SPACE
0		0				3P	35	B	36		SPACE
0		0	SPARE			125	37	A	38		SPACE
0		0				↓	39	B	40		SPACE
0		0				3P	41	B	42		SPACE
			BLDG #:	143	FLOOR:	2	ROOM:	278	NEW TAG:	N/A	
			RATINGS:	400A	120/208V	3 PHASE	4 WIRE	S.C.:	10		
			FED. FROM:	PANEL TAG: 143-NTX-02-06-BA	BLDG #:	143	ROOM #:	278	N/A	BREAKER SIZE: 4 300KCMIL + #4 AWG IN 3" C	FEEDER SIZE:
143-NDP-02-02-BA.xlsx											

1 E033


PANEL 143-NLP-03-02-8D SCHEDULE
SCALE: NTS

UNIVERSITY OF TORONTO											
143-NDP-02-02-BB											
BLDG #:	143	PANEL TAG	DATE MODIFIED: 2025-02-13								
CONNECTED LOAD (W)	DEMAND FACTOR	TOTAL DEMAND	DESCRIPTION (Item, Room Number(s)):			BKR (A)	CT	CT	BKR (A)	DESCRIPTION (Item, Room Number(s)):	CONNECTED LOAD (W)
453	1.00	453	PANEL 143-NLP-02-02-BA, 231B			100	1	A	2	100	PANEL 143-NLP-03-02-BB, 359A
453	1.00	453				↓	3	B	4	↓	540.00
453	1.00	453				3P	5	B	6	3P	540.00
1564	1.00	1564	PANEL 143-NLP-02-02-BB, 280			100	7	A	8	100	PANEL 143-NLP-03-02-BC, 399D
1564	1.00	1564				↓	9	B	10	↓	1063.00
1564	1.00	1564				3P	11	B	12	3P	1063.00
0		0	SPARE			100	13	A	14		SPACE
0		0				↓	15	B	16		SPACE
0		0				3P	17	B	18		SPACE
0		0	SPARE			100	19	A	20		SPACE
0		0				↓	21	B	22		SPACE
0		0				3P	23	B	24		SPACE
0		0	SPARE			100	25	A	26		SPACE
0		0				↓	27	B	28		SPACE
0		0				3P	29	B	30		SPACE
0		0	SPARE			100	31	A	32		SPACE
0		0				↓	33	B	34		SPACE
0		0				3P	35	B	36		SPACE
0		0	SPARE			100	37	A	38		SPACE
0		0				↓	39	B	40		SPACE
0		0				3P	41	B	42		SPACE
			BLDG #:	143	FLOOR:	2	ROOM:	278	NEW TAG:	10	
			RATINGS:	400A	120/208V	3 PHASE	4 WIRE	S.C.:	10		
			FED. FROM:	PANEL TAG: 143-NTX-02-06-BA	BLDG #:	143	ROOM #:	278	N/A	BREAKER SIZE: 4 300KCMIL + #4 AWG IN 3" C	FEEDER SIZE:
143-NDP-02-02-BB.xlsx											

1 E033

PANEL LP-EMA
SCALE: NTS

|--|



REVISION	
NO.	DESCRIPTION
1	2024-10-04 ISSUED FOR 50%
2	2024-11-15 PERMIT
3	2024-12-04 ISSUED FOR FAS REVIEW
4	2024-12-23 ISSUED FOR FAS REVIEW
5	2025-01-24 ISSUED FOR PEER REVIEW
6	2025-01-31 ISSUED FOR BID

SCOPE ITEM	AUDIOVISUAL CONTRACTOR (A.V.C.)	ELECTRICAL CONTRACTOR (E.C.)	GENERAL CONTRACTOR (G.C.)	COMMUNICATIONS CONTRACTOR (C.C.)
AV SYSTEMS CONDUIT, BACKBOXES AND CABLE TRAYS	-	PROVIDE PULL-READY SYSTEM INCLUDING ALL CONDUIT, BACKBOXES AND CABLE TRAYS. ALL CONDUITS TO BE COMPLETE WITH PULLSTRING.	-	-
AV WALLBOX CONNECTOR PLATES, CUSTOM OR STANDARD	PROVIDE, FINISH PER ARCHITECT'S INSTRUCTIONS	-	-	-
AV FLOORBOXES	MODIFY PLATES TO SUIT FLOORBOX AND INSTALL	PROVIDE FLOORBOX, COORDINATE BOX TYPE WITH AV CONSULTANT; SUPPLY SAMPLE IF REQUESTED, SUPPLY BLANK PLATES TO AV CONTRACTOR	-	-
AV SYSTEMS CABLE (LOW VOLTAGE, INCLUDING NETWORK CABLING FOR AV SYSTEMS)	PROVIDE	-	-	-
AC OUTLETS FOR DISPLAYS, PROJECTORS, AV EQUIPMENT, FLOORBOXES, ETC	-	PROVIDE	-	-
DIRECT POWER CONNECTIONS FOR AV SYSTEMS RACKS	PROVIDE DISTRIBUTION WITHIN RACK	PROVIDE POWER CIRCUITS AS REQUIRED AT LOCATIONS NOTED ON DRAWINGS. COORDINATE LOCATIONS WITH AV CONTRACTOR PROVIDE SEPARATE NEUTRAL CONDUCTOR FOR EACH CIRCUIT.	-	-
LAN DROPS FOR OWNER SUPPLIED NETWORK	SPECIFY LOCATIONS AND COORDINATE WITH C.C.	-	-	PROVIDE. REFER TO COORDINATION MATRIX FOR LOCATIONS AND QUANTITIES
PATCH CABLING TO CLIENT NETWORK FOR AV DEVICES	INSTALL	-	-	SUPPLY
MILLWORK FURNITURE (TABLES, RACK ENCLOSURES, LECTERNS AND CREDENZAS)	FIT-UP MILLWORK WITH AV DEVICES. COORDINATE WITH DESIGNERS, G.C., E.C. AND FURNITURE/MILLWORK MANUFACTURER	PROVIDE POWER AND LAN CONNECTIVITY SHOWN ON DRAWINGS AND INSTALL ROUGH-INS AS REQUIRED	PROVIDE AND COORDINATE CUTOUTS, WIRING AND DEVICE PLACEMENTS	-
DISPLAY AND PROJECTOR MOUNTING	SUPPLY AND INSTALL STANDARD OR CUSTOM BRACKETS AS REQUIRED	-	PROVIDE BLOCKING AND MISCELLANEOUS METALS AS REQUIRED	-
CEILING MOUNTED LOUDSPEAKER BACKBOXES INTO DRYWALL CEILINGS	PROVIDE	PROVIDE CONDUIT TO SPEAKER BACKBOXES. COORDINATE WITH AV CONTRACTOR ON SITE	PROVIDE CEILING SPEAKER CUTOUTS	-
CEILING MOUNTED LOUDSPEAKERS INTO TILE CEILINGS	PROVIDE	-	PROVIDE CEILING SPEAKER CUTOUTS	-
AV SYSTEMS ELECTRONICS, HARDWARE, RACKS PERMANENT AND PORTABLE	PROVIDE; REUSE OWNER SUPPLIED EQUIPMENT AS NOTED	-	-	-
AV CONTROL SYSTEM PAGE DESIGN AND TESTING	PROVIDE; WRITE ALL PROGRAMMING CODE; DESIGN AND IMPLEMENT	-	-	-
LOW VOLTAGE RELAY CONTROLLERS (LVC) FOR MOTORIZED PROJECTION SCREENS AND LIFTS	SUPPLY LVC TO E.C.; PROVIDE LOW VOLTAGE CONTROL CABLE	PROVIDE HIGH VOLTAGE CABLE, TERMINATIONS AND LABOR AS REQUIRED	PROVIDE ACCESS HATCH AS REQUIRED FOR BACKBOX ACCESS	-
INTELLIGENT LIGHTING AND BLIND/SHADE SYSTEMS	CONNECT AV CONTROL SYSTEM TO RS-232 PROTOCOL CONVERTER. COORDINATE INSTALLATION LOCATION WITH E.C.	PROVIDE LIGHTING/BLIND SYSTEM TO RS-232 PROTOCOL CONVERTER. COORDINATE INSTALLATION LOCATION WITH A.V.C.	PROVIDE BLINDS SYSTEM AND SHADE MOTOR GROUP CONTROLLERS.	-
CEILING PROJECTION SCREENS	PROVIDE	PROVIDE HIGH VOLTAGE CABLE TO LVC	FINISH CEILING AFTER INSTALLATION.	-
FIRE ALARM CONNECTION	PROVIDE MUTE FUNCTIONALITY ON ALL SOUND SYSTEMS. TO BE TRIGGERED ON ACTIVATION OF FIRE ALARM.	PROVIDE FACP DRY CONTACT RELAY CONNECTION TO AV CONTRACTOR	-	-
THE SCOPE OF WORK OF THE TRADES AS IT RELATES TO AUDIO VISUAL SYSTEMS IS DESCRIBED IN THE TABLE ABOVE. THE TERM "PROVIDE" MEANS "SUPPLY, INSTALL, TERMINATE, TEST AND COMMISSION"				



SEAL :



PROJECT :
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS :
AV DIVISION OF
RESPONSIBILITY MATRIX

PROJECT NUMBER :
21590.003
DRAWING SCALE :
1 : 1500





DRAWN BY :
Author

CHECKED BY :
Checker

DATE:
Issue Date

SHEET NO :
E035


REV :
6

DEVICE	MOUNTING HEIGHT	DEVICE	MOUNTING HEIGHT
	1100 MM (43 IN.) AFF		WALL OR CEILING MOUNT ABOVE DOOR AS RECOMMENDED BY MANUFACTURER
	1100 MM (43 IN.) AFF		CEILING MOUNT ABOVE DOOR

6 DOOR DETAIL NOTES
E036




5 DOOR DETAIL 3



3 DOOR DETAIL 1







4 DOOR DETAIL 2



5 DOOR DETAIL 3



1 DEVICE MOUNTING HEIGHTS


DEVICE	MOUNTING HEIGHT	DEVICE	MOUNTING HEIGHT	DEVICE	MOUNTING HEIGHT	DEVICE	MOUNTING HEIGHT
	1100 MM (43 IN.) AFF		1100 MM (43 IN.) AFF		WALL OR CEILING MOUNT ABOVE DOOR AS RECOMMENDED BY MANUFACTURER		CEILING MOUNT ABOVE DOOR










GENERAL NOTES:

1. REFER TO DOOR DETAIL NOTES FOR ADDITIONAL INFORMATION.


2. DOOR HANDLES SHOWN ARE DIAGRAMMATIC. REFER TO DOOR HARDWARE SCHEDULE FOR EXACT DOOR HANDLE TYPE.

2 SECURITY, DOOR HARDWARE, ELECTRICAL AND COMMUNICATIONS CONTRACTORS
E036 RESPONSIBILITY MATRIX FOR SECURITY DEVICES INSTALLATION






KEY PLAN:



REVISION	
NO.	DESCRIPTION
1	2024-10-04 ISSUED FOR 50%
2	2024-11-15 PERMIT
3	2024-12-04 ISSUED FOR F&S REVIEW
4	2024-12-23 ISSUED FOR F&S REVIEW
5	2025-01-24 ISSUED FOR PEER REVIEW
6	2025-01-31 ISSUED FOR BID



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER






214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
STANDARD DETAILS -
SECURITY

PROJECT NUMBER:
21590.003
DRAWING SCALE:
NTS.

DRAWN BY: CHECKED BY: DATE:
Author Checker Issue Date

SHEET NO.: REV:
E037 6



GENERAL NOTES:

1. ROUTE ALL ACCESS CONTROL DEVICE WIRING CONTINUOUSLY TO THE POINT OF TERMINATION. NO SPLICES ARE PERMITTED.
2. COORDINATE INSTALLATION WITH DOOR, DOOR HARDWARE AND ELECTRICAL CONTRACTORS.
3. BOND ALL ACCESS CONTROL PANELS AND THE SHIELD OF ALL SHIELDED CABLES TO GROUND WITH MANUFACTURER RECOMMENDED GROUND WIRE.
4. PROVIDE LOCK AND KEY TO FACILITATE SECURING ACCESS CONTROL SYSTEM DEVICES AND WIRING WITHIN ACCESS CONTROL PANEL ENCLOSURE AND TROUGHS.
5. PROVIDE DOOR CONTACTS ON ALL ACCESS CONTROL ENCLOSURES AND TROUGHS DOORS. CONNECT ALL DOOR CONTACTS TO THE ACCESS CONTROL SYSTEM TO FACILITATE MONITORING OF DOOR POSITIONS.
6. QUANTITIES OF ACCESS CONTROL CONTROLLERS, ENCLOSURES AND POWER SUPPLIES SHOWN INDICATES SCHEMATIC AND CONNECTIVITY REQUIREMENTS ONLY. PROVIDE ALL ACCESS CONTROL CONTROLLERS, ENCLOSURES AND POWER SUPPLIES AS REQUIRED TO FACILITATE COMPLETE OPERATION OF THE ACCESS CONTROL SYSTEM.


NOTES:

- (N-1) 120V 15A CIRCUITS FROM UPS OR EMERGENCY POWER SOURCE (TYP.) COORDINATE DIRECT CONNECTION TO POWER SUPPLIES WITH ELECTRICAL CONTRACTOR.
- (N-2) PROVIDE CONDUITS AS REQUIRED TO INTERCONNECT ACCESS CONTROL PANEL ENCLOSURES (TYP.)
- (N-3) ACCESS CONTROL CONTROLLER ENCLOSURE (TYP.). QUANTITIES SHOWN INDICATES SCHEMATIC AND CONNECTIVITY REQUIREMENTS ONLY. PROVIDE ALL ENCLOSURES AS REQUIRED TO HOUSE AND PROTECT ALL CONTROLLERS. ENCLOSURES SHALL BE COMPLETE WITH TAMPER SWITCHES AND KEY LOCK.
- (N-4) 1219MM (48 1/8") X 2438MM (96 3/8") (60") FIRE RETARDANT PLYWOOD BACKBOARD. PROVIDE APPROPRIATE NUMBER OF PLYWOOD BACKBOARD TO MOUNT ALL ENCLOSURES AND POWER SUPPLIES. ENCLOSURES AND POWER SUPPLIES.
- (N-5) PROVIDE APPROPRIATELY SIZED METAL TROUGH WITH LOCKABLE HINGED COVER AS REQUIRED TO HOUSE AND PROTECT ALL WIRING FROM CONDUITS TO ENCLOSURES (TYP.)
- (N-6) 120V 15A CIRCUITS FROM NON-EMERGENCY BUILDING POWER SOURCE (TYP.) COORDINATE DIRECT CONNECTION TO POWER SUPPLIES WITH ELECTRICAL CONTRACTOR.
- (N-7) INTRUSION DETECTION CONTROLLER ENCLOSURE (TYP.). QUANTITIES SHOWN INDICATES SCHEMATIC AND CONNECTIVITY REQUIREMENTS ONLY. PROVIDE ALL ENCLOSURES AS REQUIRED TO HOUSE AND PROTECT ALL CONTROLLERS. ENCLOSURES SHALL BE COMPLETE WITH TAMPER SWITCHES AND KEY LOCK. PROVIDE GSM AND INTERNET COMMUNICATIONS CONTROLLERS TO RELAY ALARMS TO ALARM MONITORING COMPANY. COORDINATE WITH OWNER AND ALARM MONITORING COMPANY FOR PROVISIONING AND INSTALLATION OF ALARM MONITORING CIRCUITS AND COMMISSION THE COMMUNICATIONS CONTROLLERS INTO SERVICE.

1 ACCESS CONTROL ENCLOSURE MOUNTING DETAILS



KEY PLAN:



REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



ENFORM
architects

ENFORM Architects Inc.
1284 Sterling Road, Suite 302B
Toronto, Ontario, Canada M6R 2B7
416-546-7523
www.enformarchitects.com

SEAL:

OWNER:



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
STANDARD DETAILS -
SECURITY

PROJECT NUMBER:
21590.003

DRAWING SCALE:

NTS.



DRAWN BY:	CHECKED BY:	DATE:
Author	Checker	Issue Date

SHEET NO:

E038

REV:

6



REVISION	
NO.	DESCRIPTION
1	2024-10-04 ISSUED FOR 50%
2	2024-11-15 PERMIT
3	2024-12-04 ISSUED FOR FAS REVIEW
4	2024-12-23 ISSUED FOR FAS REVIEW
5	2025-01-24 ISSUED FOR FAS REVIEW
6	2025-01-31 ISSUED FOR BID



SEAL:



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
SITE PLAN - ELECTRICAL


PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 200

DRAWN BY: CHECKED BY: DATE:
Author Checker Issue Date


SHEET NO.: REV:
E101 6

KEY PLAN:



REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



DRAWING NOTES:


- (N1) OUTLETS TO BE SURFACE MOUNTED.
- (N2) PROVIDE SHUNT TRIP BREAKER FOR APPLIANCE/OUTLET UNDER HOOD. UPON ACTIVATION OF FIRE SUPPRESSION SYSTEM, SIGNAL SHALL BE SEND TO SHUNT TRIP BREAKERS TO TURN OFF.
- (N3) REFER TO SITE 020 FOR DETAIL OF TYPICAL BARRIER FREE/UNIVERSAL WASHROOM
- (N4) INDOOR UNIT IS POWER VIA THE CONDENSER ON ROOF. ALLOW FOR HARDWARE CONNECTIONS AND DISCONNECTS AT ALL UNITS. PIPE AND WIRE TO FOLLOW MECHANICAL ROUTING. ALLOW FOR ALL ASSOCIATED COSTS. COORDINATE WITH SHOP DRAWINGS AND THE MECHANICAL CONTRACTOR ON SITE PRIOR TO ROUGH-IN.
- (N5) PROVIDE SUITABLE SIZED PULL BOX FOR REQUIRED CONDUITS. REFER TO AV DRAWINGS SAY 301 FOR ADDITIONAL INFORMATION.
- (N6) SINGLE GANG JUNCTION BOX FOR CAMERA. CONFIRM EXACT LOCATION ON SITE WITH AV VENDOR PRIOR TO ROUGH-IN.
- (N7) PROVIDE TWO ADDITIONAL FIRE ALARM ZONES. TROUBLE AND ALARM SIGNALS FOR FIRE SUPPRESSION SYSTEM. UPDATE EXISTING FIRE ALARM PANEL AND FIRE ALARM MANUFACTURER PANEL. AS REQUIRED. COORDINATE WITH BASE BUILDING FIRE ALARM CONTRACTOR FOR TIE-INS TO EXISTING FIRE ALARM SYSTEM. REFER TO ECOLOGIZER DOCUMENTATION FOR ADDITIONAL INFORMATION.

- (N8) PROVIDE 12" IN SLACK/CEILING SPACE BELOW FOR AUTOODOR PUSHBUTTON. CONFIRM ROUTING ON SITE. COORDINATE THIS SCOPE OF WORK WITH GC PRIOR TO WORK COMMENCING.

GENERAL NOTES:

- 1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
- 2. CIRCUITING IN PART IS DIAGRAMMATIC INTENDED TO SHOW GENERAL CIRCUIT ARRANGEMENT AND PANEL DESIGNATION.
- 3. PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILING. EX CABLES IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. BY CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES OR EQUIPMENT WITH A MAXIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PANT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXT. SIZES, OCCUPANCY SENSORS, EX. SIGNS, CAMERAS, WIPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEMS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
- 4. VERIFY EXACT POWER REQUIREMENTS AND RECEPTACLE TYPES FOR SPECIAL EQUIPMENT WITH MANUFACTURER PRIOR TO INSTALLATION. PROVIDE HARDWARE CONNECTIONS FOR DOWNWHERES AND CORPERS ETC. IN LIEU OF RECEPTACLES OR VICE VERSA, AS REQUIRED.
- 5. REFER TO INTERIOR DESIGNER/ARCHITECT DRAWINGS FOR THE COLOUR OF COVERPLATES AND MOUNTING HEIGHTS.
- 6. MARK UP OUTLET AND DEVICE LOCATIONS AND OBTAIN APPROVAL BY DESIGN CONSULTANT PRIOR TO INSTALLATION.
- 7. PROVIDE SUITABLE LABELS ON ALL RECEPTACLES AND SYSTEM FURNITURE FEEDS. LABELS TO INCLUDE BOTH PANEL AND CIRCUIT DESIGNATION. REVIEW LABEL SIZE AND TYPE WITH CONSULTANT PRIOR TO INSTALLATION.
- 8. CONFIRM ELECTRICAL REQUIREMENTS AND EXACT LOCATION OF ALL MECHANICAL/COMMUNICATIONARY EQUIPMENT WITH MECHANICAL/COMMUNICATIONARY DRAWINGS AND CONTRACTOR PRIOR TO ROUGH-INS. NO ADDITIONAL COSTS WILL BE APPROVED FOR ANY REVISIONS/MODIFICATIONS REQUIRED BY ANY TRADE OR CONTRACTOR DUE TO THE LACK OF COORDINATION BETWEEN TRADES AND CONTRACTORS.
- 9. ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
- 10. COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/DC DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
- 11. UNLESS OTHERWISE NOTED, POWER TO BE FEED FROM PANELS LOCATED ON THIS FLOOR.
- 12. ALLOW FOR THE REWORKING OF EXISTING CONDUIT/FEEDERS TO ACCOMMODATE NEW SCOPE OF WORK AND/OR INTERFERENCES.

KEY PLAN:



REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-24	ISSUED FOR P&S REVIEW
4	2024-12-23	ISSUED FOR P&S REVIEW
5	2025-01-24	ISSUED FOR P&S REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:



PROJECT:
HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LEVEL 01 - POWER PLAN


PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100



DRAWN BY: Author
CHECKED BY: Checker
DATE: Issue Date

SHEET NO.: **E301**

REV: **6**



- (N1) FEEDER CONDUITS FOR POWER, DATA, AV, OR SECURITY AT THIS LOCATION TO BE RUN FROM GROUND FLOOR CEILING ABOVE.
- (N2) EXPOSED CONDUITS SHALL NOT BE PERMITTED ON ABOVE CEILING IN THIS CORRIDOR.
- (N3) REFER TO DETAIL 3E020 FOR DETAIL OF TYPICAL BARRIER FREE UNIVERSAL WASHROOM.
- (N4) INDOOR UNIT IS POWER VIA THE CONDENSER ON ROOF. ALLOW FOR HARDWARE CONNECTIONS AND DISCONNECTS AT ALL UNITS. PIPE AND WIRE TO FOLLOW MECHANICAL ROUTING. ALLOW FOR ALL ASSOCIATED COSTS. COORDINATE WITH SHOP DRAWINGS AND THE MECHANICAL CONTRACTOR ON SITE PRIOR TO PROJECT-IN.
- (N5) OUTLETS FOR REJECTION IN WALL RECESS. COORDINATE LOCATION ON SITE

[illegible]

OWNER:

 UNIVERSITY OF
TORONTO


PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST,
TORONTO, ON M5T 3A1

SHEET CONTENTS :

LEVEL 02 - POWER PLAN

PROJECT NUMBER :		21590.003	
DRAWING SCALE :		As indicated	
DRAWN BY :	CHECKED BY :	DATE:	
Author	Checker	Issue Date	
SHEET NO :			REV :





DRAWING NOTES:

- PROVIDE BRONZE COVER PLATE FOR OUTLETS/SWITCHES IN THIS AREA IN CONJUNCTION WITH ARCHITECTURAL WOOD PANEL SYSTEM. COORDINATE EXACT COLOUR WITH ARCHITECTURAL.
- DISCONNECT SWITCH WITH AUX CONTACT.
- PROVIDE POWER TO MEDICAL FRIDGE FROM SPLITTER PP-EM IN ROOM #909A. COORDINATE LOCATION ON SITE WITH CLIENT/IGC PRIOR TO ROUGH-IN. REFER TO SINGLE LINE DIAGRAM FOR ADDITIONAL INFORMATION.
- COORDINATE EXACT LOCATION OF DISCONNECT SWITCHES FOR ELEVATOR WITH ELEVATOR VENDOR PRIOR TO ROUGH-IN. CONFIRM REQUIRED DISCONNECT SWITCH TYPES PRIOR TO PURCHASING. CONTACT ERIC LAM (ERIC.LAM@BA.COM) X 438-200-9405.
- INDOOR UNIT IS POWER VIA THE CONDENSER ON ROOF. ALLOW FOR HARDWARE CONNECTIONS AND DISCONNECTS AT ALL UNITS. PIPE AND WIRE TO FOLLOW MECHANICAL ROUTING. ALLOW FOR ALL ASSOCIATED COSTS. COORDINATE WITH EXIST DRAWING AND THE MECHANICAL CONTRACTOR ON SITE PRIOR TO ROUGH-IN.
- PROVIDE 120V/1P, 30A UNFUSED DISCONNECT SWITCH.
- EXHAUST FAN CONTROLLED BY REVERSE ACTING THERMOSTAT. THERMOSTAT SUPPLIED BY MECHANICAL INSTALLED BY ELECTRICAL.
- HATCHED AREA INDICATES FUTURE AREA.


GENERAL NOTES:

- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
- CIRCUITING IN PART IS DIAGRAMMATIC INTENDED TO SHOW GENERAL CIRCUIT ARRANGEMENT AND PANEL DESIGNATION.
- PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILING. BX CABLE IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. BX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES OR EQUIPMENT WITH A MAXIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PAINT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERA, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEAR SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
- VERIFY EXACT POWER REQUIREMENTS AND RECEPTACLE TYPES FOR SPECIAL EQUIPMENT WITH MANUFACTURER PRIOR TO INSTALLATION. PROVIDE HARDWARE CONNECTIONS FOR DISHWASHERS AND COFFERS ETC. IN LIEU OF RECEPTACLES OR VICE VERSA, AS REQUIRED.
- REFER TO INTERIOR DESIGNER/ARCHITECT DRAWINGS FOR THE COLOUR OF COVERPLATES AND MOUNTING HEIGHTS.
- MARK UP OUTLET AND DEVICE LOCATIONS AND OBTAIN APPROVAL BY DESIGN CONSULTANT PRIOR TO INSTALLATION.
- PROVIDE SUITABLE LABELS ON ALL RECEPTACLES AND SYSTEM FURNITURE FEEDS LABELS TO INCLUDE BOTH PANEL AND CIRCUIT DESIGNATION. REVIEW LABEL SIZE AND TYPE WITH CONSULTANT PRIOR TO INSTALLATION.
- CONFIRM ELECTRICAL REQUIREMENTS AND EXACT LOCATION OF ALL MECHANICAL/COMMUNICATIONARY EQUIPMENT WITH MECHANICAL/COMMUNICATIONARY DRAWINGS AND CONTRACTOR PRIOR TO ROUGH-INS. NO ADDITIONAL COSTS WILL BE APPROVED FOR ANY REVISIONS/ADJUSTMENTS REQUIRED BY ANY TRADE OR CONTRACTOR DUE TO THE LACK OF COORDINATION BETWEEN TRADES AND CONTRACTORS.
- ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
- COORDINATE ALL WORK TO SUB PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/MECHANICAL. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
- UNLESS OTHERWISE NOTED, POWER TO BE FED FROM PANELS LOCATED ON THIS FLOOR.
- ALLOW FOR THE NEWWORKING OF EXISTING CONDUIT/FEEDERS TO ACCOMMODATE NEW SCOPE OF WORK AND/OR INTERFERENCES.





- GENERAL NOTES:
1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
 2. SHOWN IS PROPOSED ROUTING ONLY. EXACT ROUTING TO BE CONFIRMED ON SITE.
 3. MAIN CONDUITS SHALL BE RUN ALONG CORRIDOR WHERE POSSIBLE.
 4. PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILINGS. BX CABLES IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. BX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES OR EQUIPMENT WITH A MAXIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PANT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEMS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
 5. ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
 6. COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/CC DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
 7. THESE DRAWINGS WILL BE READ IN CONJUNCTION WITH COMMUNICATIONS SECURITY AND AV DRAWINGS FOR COMPLETE SCOPE OF WORK FOR CONDUIT PATHWAYS. ADDITIONAL FEES WILL NOT BE PERMITTED DUE TO LACK OF COORDINATION.



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:




PROJECT:
HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1
SHEET CONTENTS:
LEVEL 00 - PATHWAY LAYOUT


PROJECT NUMBER: 21590.003		
DRAWING SCALE: 1 : 100		
DRAWN BY: Author	CHECKED BY: Checker	DATE: Issue Date
SHEET NO.: E306	REV: 6	



REFERENCE PICTURE OF EXISTING CRAWLSPACE



- GENERAL NOTES:
1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
 2. SHOWN IS PROPOSED ROUTING ONLY. EXACT ROUTING TO BE CONFIRMED ON SITE.
 3. MAIN CONDUITS SHALL BE RUN ALONG CORRIDOR WHERE POSSIBLE.
 4. PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILING. BX CABLEING IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. BX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES OR EQUIPMENT WITH A MAXIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PANT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WIPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEMS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
 5. ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
 6. COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/CC DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
 7. THESE DRAWINGS WILL BE READ IN CONJUNCTION WITH COMMUNICATIONS SECURITY AND AV DRAWINGS FOR COMPLETE SCOPE OF WORK FOR CONDUIT PATHWAYS. ADDITIONAL FEES WILL NOT BE PERMITTED DUE TO LACK OF COORDINATION.



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR FAS REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:



PROJECT:
**HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER**

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LEVEL 01 - PATHWAY LAYOUT

PROJECT NUMBER:
21590.003

DRAWING SCALE:

1 : 100


DRAWN BY: CHECKED BY: DATE: REV:

Author Checker Issue Date


SHEET NO:

E307

6



- GENERAL NOTES:
1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
 2. SHOWN IS PROPOSED ROUTING ONLY. EXACT ROUTING TO BE CONFIRMED ON SITE.
 3. MAIN CONDUITS SHALL BE RUN ALONG CORRIDOR WHERE POSSIBLE.
 4. PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILINGS. BX CABLEING IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. BX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES OR EQUIPMENT WITH A MAXIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PANT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEMS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
 5. ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
 6. COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/CCG DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
 7. THESE DRAWINGS WILL BE READ IN CONJUNCTION WITH COMMUNICATIONS SECURITY AND AV DRAWINGS FOR COMPLETE SCOPE OF WORK FOR CONDUIT PATHWAYS. ADDITIONAL FEES WILL NOT BE PERMITTED DUE TO LACK OF COORDINATION.



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR P&S REVIEW
4	2024-12-23	ISSUED FOR P&S REVIEW
5	2025-01-24	ISSUED FOR P&S REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:



PROJECT:
**HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER**

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LEVEL 02 - PATHWAY LAYOUT

PROJECT NUMBER:
21590.003
DRAWING SCALE:
1 : 100
DRAWN BY: Author
CHECKED BY: Checker
DATE: Issue Date

SHEET NO.:
E308
REV: 6

[illegible]

A map of the study area showing the location of the study site (shaded gray) relative to the Jettie Nordell and Jettie South streets. A north arrow is included.

REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR F&S REVIEW
4	2024-12-23	ISSUED FOR F&S REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



ENFORM Architects Inc.
128A Sterling Road, Suite 302B
Toronto, Ontario, Canada M6R 2B7
t: 647-948-7523
www.enformarchitects.com

OWNE




214 COLLEGE ST,
TORONTO, ON M5T 3A1


SHEET CONTENTS :

LEVEL 03 - PATHWAY LAYOUT

1 : 100		
DRAWN BY : Author	CHECKED BY : Checker	DATE: Issue Date

--	--






DRAWING NOTES:

GENERAL NOTES:

1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
2. CIRCUITING IN PART IS DIAGRAMMATIC INTENDED TO SHOW GENERAL CIRCUIT ARRANGEMENT AND PANEL DESIGNATION.
3. PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILINGS. EX CABLEING IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. EX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES. EQUIPMENT SHALL BE MOUNTED WITH A MINIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PAINT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEPS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
4. ALL NEW/RELOCATED/REINSTALLED BASE BUILDING STANDARD LUMINAIRES AND NEW RECESSED DOWN LIGHTS SHALL BE CHAIN HUNG AND SUPPORTED FROM THE SLAB ABOVE. PROVIDE LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
5. RELAMP EXISTING AND RELOCATED LUMINAIRES DUE TO BURNOUT CONDITIONS AND REPLACE FAULTY BALLASTS AS REQUIRED. INCLUDE IN BASE PRICE.
6. MEASURE THE ILLUMINATION OF THE FLOOR AT NIGHT WITH EMERGENCY LIGHTING ON ONLY. AND SEND A DRAWING SHOWING THE MAXIMUM AND MINIMUM LEVEL OF ILLUMINATION. TO THE CONSULTING ENGINEER. FOR REVIEW. PROVIDE WRITTEN CONFIRMATION THAT EMERGENCY LIGHTING HAS BEEN INSTALLED IN ACCORDANCE WITH CONTRACT DOCUMENTS AND LATEST EDITION OF THE ONTARIO BUILDING CODE SECTIONS 3.2.7.3 AND 3.2.14. LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
7. PROVIDE NEW PICTOGRAM (RUNNING MAN) TYPE EXIT SIGNS, FACES AND INDICATOR ARROWS AS PER DRAWINGS AND UNIVERSAL 120-347-AC. CONNECT NEW EXIT SIGNS TO THE EXIT LIGHTING CIRCUIT SERVING THIS AREA. DO NOT OVERLOAD THE CIRCUIT. ALLOW FOR FIVE (5) ADDITIONAL EXIT SIGNS PER FLOOR (COMPLETE WITH MATERIAL AND LABOUR) TO BE INSTALLED AS PER BUILDING INSPECTORS REQUIREMENTS UPON FINAL INSPECTION.
8. LOCATE AND POSITION EXIT SIGNS SUCH THAT THEY DO NOT INTERFERE WITH ADJACENT EXIT SIGNS AND EMERGENCY LIGHTING COVERAGE.
9. ENSURE THAT ALL LIGHTING FIXTURES ARE CLEAN AND ILLUMINATED BY END OF PROJECT.
10. LIGHTING FIXTURES IDENTIFIED AS EMERGENCY ARE TO BE CONNECTED SO THAT UNDER NORMAL CONDITIONS THEY WORK IN CONJUNCTION WITH THE SWITCHING AS IDENTIFIED. IN THE EVENT OF AN EMERGENCY, THESE LIGHTS ARE TO BE FORCED ON WITH THE USE OF A UL-924 LISTED RELAY. (UPON POWER FAILURE THE RELAY IS TO ACTIVATE THE LIGHTS TO FULL BRIGHTNESS).
11. REMOVE ALL PAGING/AUDIO SPEAKERS IN RENOVATED AREA NOT SHOWN ON PLANS. ALL EXISTING TO REMAIN SPEAKERS TO BE FIRE ALARM EVAC SPEAKERS ONLY.
12. ALL CEILING MOUNTED OCCUPANCY SENSORS PROVIDED AS PART OF THIS SCOPE OF WORK MUST BE LOCATED AT LEAST 6" AWAY FROM ANY SUPPLY AIR DIFFUSER AND RETURN AIR GRILLE AS PER MANUFACTURER'S RECOMMENDATION. COORDINATE INSTALLATION ON SITE WITH MECHANICAL CONTRACTOR PRIOR TO COMMENCING WORK.
13. COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGNER'S DRAWINGS. PHASING SHOWN IS FOR REFERENCE PURPOSES ONLY.
14. ALLOW FOR THE REWORKING OF EXISTING CONDUIT/FEEDERS TO ACCOMMODATE NEW SCOPE OF WORK AND/OR INTERFERENCES.

KEY PLAN:



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-24	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID




SEAL:



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1
SHEET CONTENTS:
LEVEL 01 - LIGHTING PLAN

PROJECT NUMBER: 21590.003		
DRAWING SCALE: 1 : 100		
DRAWN BY: Author	CHECKED BY: Checker	DATE: Issue Date
SHEET NO: E401	REV: 6	



AREA	ROOM #	OCCUPANCY SENSOR (WALL/CEILING)	ON/OFF	LOCAL CONTROL (SWITCH, WALL STATION, DIMMER)	NOTES
CUSTOMER ROOMS/STORAGE		WALL	AUTO ON/AUTO OFF		
WASHROOMS		CEILING	AUTO ON/AUTO OFF		LIGHTING ON EM CCT
ELECTRICAL CLOSET/ROOMS				SWITCH	LIGHTING ON EM CCT
IT CLOSET				SWITCH	LIGHTING ON EM CCT
INDIVIDUAL OFFICES	113	CEILING	MANUAL ON, AUTO OFF	3 SCENE WALL STATION	
INDIVIDUAL OFFICES		WALL	MANUAL ON, AUTO OFF	DIMMER BUILT-IN TO WALL OS	
MULTIPURPOSE ROOMS		CEILING SENSOR	MANUAL ON, AUTO OFF	5 SCENE WALL STATION	
ELEVATOR ACCESS	1	CEILING	AUTO ON/AUTO OFF	3 3A	DIM TO 50% BASED ON OCCUPANCY 3B 4A
WORK AREA (BY WINDOW)	325	CEILING (FIXTURES TO BE ON/OFF TOGETHER)	MANUAL ON, AUTO OFF	3 SCENE WALL STATION	DAYLIGHT HARVESTING ZONE
WORK AREA	327				
VESTIBULE	120V				
STAFF ACCESS	122V	CEILING (FIXTURES TO BE ON/OFF TOGETHER)	AUTO ON/AUTO OFF	3 SCENE WALL STATION	DOWNLIGHTS + LS
CORRIDOR	115K				
WAITING AREA	106				
KITCHEN	119			TOUCHSCREEN	LIGHTS IN KITCHEN AREA OPERATE INDEPENDENT OF OCCUPANCY SENSORS
WORK ROOM (PERIMETER)	115				
WORK ROOM (CENTER)	115	CEILING (FIXTURES TO BE ON/OFF TOGETHER)		TOUCH SCREEN	WHEN ROOM SENSOR IS IN LOW STATE, TOUCH SCREEN IN THESE AREAS TO DISPLAY SAME LIGHTING OPTIONS
WORK ROOM (SCREEN)	115				
RECEPTION (BY WINDOW)	107	CEILING (FIXTURES TO BE ON/OFF TOGETHER)	MANUAL ON, AUTO OFF	3 SCENE WALL STATION	DAYLIGHT HARVESTING ZONE
RECEPTION	107				

NOTE: 1. UNLESS NOTED OTHERWISE, ALL SENSORS TO BE SET TO 20 MINUTE OFF DELAY 2. MULTIPLE AREAS/ZONES CONTROLLED BY CEILING SENSORS SHALL BE ON/OFF TOGETHER WITH LOCAL CONTROL (AS SHOWN) 3. PROVIDE SHUNT TRIP RELAY AS REQUIRED FOR ROOMS WITH TOGGLE SWITCH CONTROLS AND EM LIGHTING CIRCUIT		
DEFAULT SCENE WALL STATION LEVELS		
S1	SCENE	LEVEL
	1	100
	2	75
S5	1	100
	2	75
	3	50
	4	25
	5	0
FINAL LEVELS TO BE CONFIRMED WITH CLIENT DURING SYSTEM COMMISSIONING		

- GENERAL NOTES:
- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
 - CIRCUITING IN PART IS DIAGRAMMATIC INTENDED TO SHOW GENERAL CIRCUIT ARRANGEMENT AND PANEL DESIGNATION.
 - PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILINGS. EX. CABLEING IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. EX. CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING. ARCHITECTURAL BACKGROUND MOUNT EXIST SENSORS. OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STARS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
 - ALL NEW/RELOCATED/REINSTALLED BASE BUILDING STANDARD LUMINAIRES AND NEW RECESSED DOWN LIGHTS SHALL BE CHAIN HUNG AND SUPPORTED FROM THE SLAB ABOVE. PROVIDE LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
 - RE-LAMP EXISTING AND RELOCATED LUMINAIRES DUE TO BURNOUT CONDITIONS AND REPLACE FAULTY BALLASTS AS REQUIRED. INCLUDE IN BASE PRICE.
 - MEASURE THE ILLUMINATION OF THE FLOOR AT NIGHT WITH EMERGENCY LIGHTING ON ONLY. AND SEND A REPORT SHOWING THE MAXIMUM AND MINIMUM LEVEL OF ILLUMINATION. TO THE CONSULTING ENGINEER. FOR REVIEW. PROVIDE WRITTEN CONFIRMATION THAT EMERGENCY LIGHTING HAS BEEN INSTALLED IN ACCORDANCE WITH CONTRACT DOCUMENTS AND LATEST EDITION OF THE ONTARIO BUILDING CODE SECTIONS 3.2.7.3 AND 3.2.7.4. LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
 - PROVIDE NEW PICTOGRAM (RUNNING MAN) TYPE EXIT SIGNS, FACES AND INDICATOR ARROWS AS PER DRAWINGS AND UNIVERSAL 120-VA/VA/VA. CONNECT NEW EXIT SIGNS TO THE EXIT LIGHTING CIRCUIT SERPING THIS AREA. DO NOT OVERLOAD THE CIRCUIT. ALLOW FOR FIVE (5) ADDITIONAL EXIT SIGNS PER FLOOR (COMPLETE WITH MATERIAL AND LABOUR) TO BE INSTALLED AS PER BUILDING INSPECTORS REQUIREMENTS UPON FINAL INSPECTION.
 - LOCATE AND POSITION EXIT SIGNS SUCH THAT THEY DO NOT INTERFERE WITH ADJACENT EXIT SIGNS AND EMERGENCY LIGHTING COVERAGE.
 - ENSURE THAT ALL LIGHTING FIXTURES ARE CLEAN AND ILLUMINATED BY END OF PROJECT.
 - LIGHTING FIXTURES IDENTIFIED AS EMERGENCY ARE TO BE CONNECTED SO THAT UNDER NORMAL CONDITIONS THEY WORK IN CONJUNCTION WITH THE SWITCHING AS IDENTIFIED. IN THE EVENT OF AN EMERGENCY, THESE LIGHTS ARE TO BE FORCED ON WITH THE USE OF A UL-624 LISTED RELAY. (UPON POWER FAILURE THE RELAY IS TO ACTIVATE THE LIGHTS TO FULL BRIGHTNESS).
 - REMOVE ALL PAGING/AUDIO SPEAKERS IN RENOVATED AREA NOT SHOWN ON PLANS. ALL EXISTING TO REMAIN SPEAKERS TO BE FIRE ALARM/EMVAC SPEAKERS ONLY.
 - ALL CEILING MOUNTED OCCUPANCY SENSORS PROVIDED AS PART OF THIS SCOPE OF WORK MUST BE LOCATED AT LEAST 8' AWAY FROM ANY SUPPLY AIR DIFFUSER AND RETURN AIR GRILLE AS PER MANUFACTURER'S RECOMMENDATION. COORDINATE INSTALLATION ON SITE WITH MECHANICAL CONTRACTOR PRIOR TO COMMENCING WORK.
 - COORDINATE ALL WORK TO SUI PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGNER. PHASING SHOWN IS FOR REFERENCE PURPOSES ONLY.

KEY PLAN:

NORTH

REVISION	
NO.	DATE
1	2024-10-04
2	2024-11-15
3	2024-12-04
4	2024-12-23
5	2025-01-24
6	2025-01-31

Smith + Andersen

1100 - 109 Sheppard Ave East, Toronto ON, M2N 0N9
416-467-8151 smithandandersen.com

ENFORM architects

ENFORM Architects Inc.
1284 Sheppard Road, Suite 302B
Toronto, Ontario, Canada M8R 2B7
1-877-646-7523
www.enformarchitects.com

SEAL:

OWNER:

UNIVERSITY OF TORONTO

PROJECT:

HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LEVEL 01 - LIGHTING CONTROL PLAN

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100

DRAWN BY:
Author

CHECKED BY:
Checker

DATE:
Issue Date


REV:

E401-A

6

DRAWING NOTES:

- Lighting/ceiling devices in this area to be removed and reinstalled as required to accommodate mechanical work in this area. COORDINATE THIS SCOPE OF WORK WITH MECHANICAL.



- GENERAL NOTES:**
- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
 - CIRCUITING IN PART IS DIAGRAMMATIC INTENDED TO SHOW GENERAL CIRCUIT ARRANGEMENT AND PANEL DESIGNATION.
 - PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILINGS. EX CABLEING IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. EX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES. EQUIPMENT SHALL BE MOUNTED WITH A MINIMUM HANG LENGTH OF 3 FEET / 1 METER. PAINT CONDUITS TO MATCH ARCHITECTURAL BACKGROUNDS. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH DUCTS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
 - ALL NEW/RELOCATED/REINSTALLED BASE BUILDING STANDARD LUMINAIRES AND NEW RECESSED DOWN LIGHTS SHALL BE CHAIN HUNG AND SUPPORTED FROM THE SLAB ABOVE. PROVIDE LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
 - RELAMP EXISTING AND RELOCATED LUMINAIRES DUE TO BURNOUT CONDITIONS AND REPLACE FAULTY BALLASTS AS REQUIRED. INCLUDE IN BASE PRICE.
 - MEASURE THE ILLUMINATION OF THE FLOOR AT NIGHT WITH EMERGENCY LIGHTING ON ONLY. AND SEND A DRAWING SHOWING THE MAXIMUM AND MINIMUM LEVEL OF ILLUMINATION. TO THE CONSULTING ENGINEER. FOR REVIEW. PROVIDE WRITTEN CONFIRMATION THAT EMERGENCY LIGHTING HAS BEEN INSTALLED IN ACCORDANCE WITH CONTRACT DOCUMENTS AND LATEST EDITION OF THE ONTARIO BUILDING CODE SECTIONS 3.2.7.3 AND 3.2.1.4. LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
 - PROVIDE NEW PICTOGRAM (RUNNING MAN) TYPE EXIT SIGNS, FACES AND INDICATOR ARROWS AS PER DRAWINGS AND UNIVERSAL 120-347AC. CONNECT NEW EXIT SIGNS TO THE EXIT LIGHTING CIRCUIT SERVING THIS AREA. DO NOT OVERLOAD THE CIRCUIT. ALLOW FOR FIVE (5) ADDITIONAL EXIT SIGNS PER FLOOR (COMPLETE WITH MATERIAL AND LABOUR) TO BE INSTALLED AS PER BUILDING INSPECTORS REQUIREMENTS UPON FINAL INSPECTION.
 - LOCATE AND POSITION EXIT SIGNS SUCH THAT THEY DO NOT INTERFERE WITH ADJACENT EXIT SIGNS AND EMERGENCY LIGHTING COVERAGE.
 - ENSURE THAT ALL LIGHTING FIXTURES ARE CLEAN AND ILLUMINATED BY END OF PROJECT.
 - LIGHTING FIXTURES IDENTIFIED AS EMERGENCY ARE TO BE CONNECTED SO THAT UNDER NORMAL CONDITIONS THEY WORK IN CONJUNCTION WITH THE SWITCHING AS IDENTIFIED. IN THE EVENT OF AN EMERGENCY, THESE LIGHTS ARE TO BE FORCED ON WITH THE USE OF A UL624 LISTED RELAY. (UPON POWER FAILURE THE RELAY IS TO ACTIVATE THE LIGHTS TO FULL BRIGHTNESS).
 - REMOVE ALL PAGING/AUDIO SPEAKERS IN RENOVATED AREA NOT SHOWN ON PLANS. ALL EXISTING TO REMAIN SPEAKERS TO BE FIRE ALARM EVAC SPEAKERS ONLY.
 - ALL CEILING MOUNTED OCCUPANCY SENSORS PROVIDED AS PART OF THIS SCOPE OF WORK MUST BE LOCATED AT LEAST 5' AWAY FROM ANY SUPPLY AIR DIFFUSER AND RETURN AIR GRILLE AS PER MANUFACTURER'S RECOMMENDATION. COORDINATE INSTALLATION ON SITE WITH MECHANICAL CONTRACTOR PRIOR TO COMMENCING WORK.
 - COORDINATE ALL WORK TO SUB PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGNER. DRAWINGS PHASING SHOWN IS FOR REFERENCE PURPOSES ONLY.
 - ALLOW FOR THE REWORKING OF EXISTING CONDUIT/FEEDERS TO ACCOMMODATE NEW SCOPE OF WORK AND/OR INTERFERENCES. DRAWING NOTES:
 - (L1) LIGHTING/CEILING DEVICES IN THIS AREA TO BE REMOVED AND REINSTALLED AS REQUIRED TO ACCOMMODATE MECHANICAL WORK IN THIS AREA. COORDINATE THIS SCOPE OF WORK WITH MECHANICAL.
 - (L2) EXISTING LIGHTING CONTROL IN THIS AREA TO REMAIN.
 - (L3) EXISTING LIGHT FIXTURES IN THIS AREA TO REMAIN.

KEY PLAN:

REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%.
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR P&S REVIEW
4	2024-12-23	ISSUED FOR P&S REVIEW
5	2025-01-24	ISSUED FOR P&S REVIEW
6	2025-01-31	ISSUED FOR BID

Smith + Andersen
1100 - 109 Sheppard Ave East, Toronto, ON, M2N 0N9
416-467-8151 smithandandersen.com

ENFORM
architects

ENFORM Architects Inc.
1286 Sheppard Road, Suite 302B
Toronto, Ontario, Canada M8R 2B7
416-546-7523
www.enformarchitects.com

SEAL:

OWNER:

UNIVERSITY OF TORONTO

PROJECT:

HEALTH AND WELLNESS CENTRE RENOVATION AT COLLEGER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:

LEVEL 02 - LIGHTING PLAN

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100


DRAWN BY:
Author


CHECKED BY:
Checker

DATE:
Issue Date

SHEET NO.:
E402

REV:
6





- GENERAL NOTES:**
1. THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH INTERIOR DESIGNER/ARCHITECT'S DRAWINGS FOR DIMENSIONS, HEIGHTS, CONSTRUCTION DETAILING, FINISHES AND COLOURS.
 2. CIRCUITING IN PART IS DIAGRAMMATIC INTENDED TO SHOW GENERAL CIRCUIT ARRANGEMENT AND PANEL DESIGNATION.
 3. PROVIDE EMT CONDUIT IN AREAS WITH EXPOSED CEILINGS. EX. CABLEING IS NOT ACCEPTABLE UNLESS OTHERWISE NOTED. BX CABLES MAY BE USED FOR FINAL CONNECTIONS TO LIGHTING FIXTURES. EQUIPMENT SHALL BE MOUNTED WITH A MINIMUM HORIZONTAL RUN LENGTH OF 3 FEET / 1 METER. PAINT CONDUITS TO MATCH ARCHITECTURAL BACKGROUND. MOUNT EXIT SIGNS, OCCUPANCY SENSORS, EXIT SIGNS, CAMERAS, WAPS AND ALL OTHER CEILING MOUNTED DEVICES WITH STEMS SUCH THAT THEY ARE ON THE SAME PLANE AS SUSPENDED LIGHTING FIXTURES. COORDINATE CEILING AND WALL HEIGHTS WITH INTERIOR DESIGNER DRAWINGS.
 4. ALL NEW/RELOCATED/REINSTALLED BASE BUILDING STANDARD LUMINAIRES AND NEW RECESSED DOWN LIGHTS SHALL BE CHAIN HUNG AND SUPPORTED FROM THE SLAB ABOVE. PROVIDE LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
 5. RELAMP EXISTING AND RELOCATED LUMINAIRES DUE TO BURNOUT CONDITIONS AND REPLACE FAULTY BALLASTS AS REQUIRED. INCLUDE IN BASE PRICE.
 6. MEASURE THE ILLUMINATION OF THE FLOOR AT NIGHT WITH EMERGENCY LIGHTING ON ONLY. AND SEND A DRAWING SHOWING THE MAXIMUM AND MINIMUM LEVEL OF ILLUMINATION. TO THE CONSULTING ENGINEER. FOR REVIEW. PROVIDE WRITTEN CONFIRMATION THAT EMERGENCY LIGHTING HAS BEEN INSTALLED IN ACCORDANCE WITH CONTRACT DOCUMENTS AND LATEST EDITION OF THE ONTARIO BUILDING CODE SECTIONS 3.2.7.3 AND 3.2.14. LETTER TO BE INCLUDED AS PART OF CLOSE-OUT DOCUMENT SUBMITTAL PACKAGE.
 7. PROVIDE NEW PICTOGRAM (RUNNING MAN) TYPE EXIT SIGNS. FACES AND INDICATOR ARROWS AS PER DRAWINGS AND UNIVERSA 120-347AC. CONNECT NEW EXIT SIGNS TO THE EXIT LIGHTING CIRCUIT SERVING THIS AREA. DO NOT OVERLOAD THE CIRCUIT. ALLOW FOR FIVE (5) ADDITIONAL EXIT SIGNS PER FLOOR (COMPLETE WITH MATERIAL AND LABOUR) TO BE INSTALLED AS PER BUILDING INSPECTORS REQUIREMENTS UPON FINAL INSPECTION.
 8. LOCATE AND POSITION EXIT SIGNS SUCH THAT THEY DO NOT INTERFERE WITH ADJACENT EXIT SIGNS AND EMERGENCY LIGHTING COVERAGE.
 9. ENSURE THAT ALL LIGHTING FIXTURES ARE CLEAN AND ILLUMINATED BY END OF PROJECT.
 10. LIGHTING FIXTURES IDENTIFIED AS EMERGENCY ARE TO BE CONNECTED SO THAT UNDER NORMAL CONDITIONS THEY WORK IN CONJUNCTION WITH THE SWITCHING AS IDENTIFIED. IN THE EVENT OF AN EMERGENCY, THESE LIGHTS ARE TO BE FORCED ON WITH THE USE OF A UL624 LISTED RELAY. (UPON POWER FAILURE THE RELAY IS TO ACTIVATE THE LIGHTS TO FULL BRIGHTNESS).
 11. REMOVE ALL PAGING/AUDIO SPEAKERS IN RENOVATED AREA NOT SHOWN ON PLANS. ALL EXISTING TO REMAIN SPEAKERS TO BE FIRE ALARM EVAC SPEAKERS ONLY.
 12. ALL CEILING MOUNTED OCCUPANCY SENSORS PROVIDED AS PART OF THIS SCOPE OF WORK MUST BE LOCATED AT LEAST 5' AWAY FROM ANY SUPPLY AIR DIFFUSER AND RETURN AIR GRILLE AS PER MANUFACTURER'S RECOMMENDATION. COORDINATE INSTALLATION ON SITE WITH MECHANICAL CONTRACTOR PRIOR TO COMMENCING WORK.
 13. COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/DC DRAWINGS. PHASING SHOWN IS FOR REFERENCE PURPOSES ONLY.

DRAWING NOTES:

(Hatched Area) WALLS SHOWN IN THE HATCHED AREA ARE FOR REFERENCE ONLY. SPACE WILL BE IN SHELL CONDITION.

KEY PLAN:

REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%.
2	2024-11-15	PERMIT
3	2024-12-24	ISSUED FOR PER REVIEW
4	2024-12-23	ISSUED FOR PER REVIEW
5	2025-01-24	ISSUED FOR PER REVIEW
6	2025-01-31	ISSUED FOR BID

OWNER

UNIVERSITY OF TORONTO

PROJECT:

HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:

LEVEL 03 - LIGHTING PLAN

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100

DRAWN BY:
Author

CHECKED BY:
Checker

DATE:
Issue Date

SHEET NO.:
E403


REV:
6


AREA	ROOM #	OCCUPANCY SENSOR	ON/OFF	LOCAL CONTROL	NOTES
CURTAINAL ROOMS/STORAGE		WALL	AUTO ON/AUTO OFF	[SWITCH, WALL SWITCH, DIMMER]	
WASHROOMS		CEILING	AUTO ON/AUTO OFF		LIGHTING ON EM CCT
BE WASHROOM & SHOWER	399A			TOGGLE SWITCH	LIGHTING ON EM CCT
ELECTRICAL CLOSET/ROOMS				TOGGLE SWITCH	LIGHTING ON EM CCT
IT LOBBY				TOGGLE SWITCH	LIGHTING ON EM CCT
LOBBY	360V	CEILING	AUTO ON/AUTO OFF		DM TO 50% BASED ON OCCUPANCY
CONSULTING/EXAM ROOMS		WALL	MANUAL ON/AUTO OFF	DIMMER BUILT-IN TO WALL GS	
ELEVATOR ACCESS		CEILING	AUTO ON/AUTO OFF		DM TO 50% BASED ON OCCUPANCY
ELEVATOR VESTIBULE	327V	CEILING	AUTO ON/AUTO OFF		DM TO 50% BASED ON OCCUPANCY
STAFF CORRIDOR	320K			DIMMER	
LOUNGE	307	CEILING	AUTO ON/AUTO OFF		DM TO 50% BASED ON OCCUPANCY
PUBLIC CORRIDOR	305K			DIMMER	
CORRIDOR	340K			DIMMER	
SUB-WAITING AREA	344,352	CEILING	AUTO ON/AUTO OFF		
DAY CORRIDOR	357K			DIMMER	
WAITING AREA	360			DIMMER	
CORRIDOR	370K	CEILING	AUTO ON/AUTO OFF		DM TO 50% BASED ON OCCUPANCY
VACCINE SEATING AREA	377			DIMMER	
CORRIDOR	397K			DIMMER	

MEETING/LUNCH	398	CEILING (FIXTURES TO BE ON/OFF TOGETHER)	AUTO ON/AUTO OFF	DIMMER	AUTO ON TO 50%
LOCKERS	399				
MEETING/LUNCH (A FIXTURE)	398		MANUAL ON/AUTO OFF	WALL SWITCH	UNDER CABINET LIGHT

NOTE:
1. UNLESS NOTED OTHERWISE, ALL SENSORS TO BE SET TO 20 MINUTE OFF DELAY
2. MULTIPLE ZONE ZONES CONTROLLED BY CEILING SENSORS SHALL BE ON/OFF TOGETHER WITH LOCAL CONTROL (AS SHOWN)
3. PROVIDE SHUNT TRIP RELAY AS REQUIRED FOR ROOMS WITH TOGGLE SWITCH CONTROLS AND EM LIGHTING CIRCUIT

DEFAULT SCENE WALL SWITCH LEVELS			
	SCENE	LEVEL	
35	1	100	FINAL LEVELS TO BE CONFIRMED WITH CLIENT DURING SYSTEM COMMISSIONING
	2	75	
	3	50	
55	1	100	
	2	75	
	3	50	
5	1	100	
	2	75	
	3	50	





- SECURITY NOTES:
- (S-1) PANIC BUTTONS SHALL BE CONNECTED TO THE NEAREST VIDEO SURVEILLANCE CAMERA. EXACT MOUNTING LOCATIONS OF THE PANIC BUTTONS AND THE PANIC RESET BUTTONS SHALL BE COORDINATED WITH THE CLIENT AND ARCHITECT PRIOR TO INSTALLATION. SECURITY CONTRACTOR SHALL INSURE THAT THE UNDER-DESK MOUNTED PANIC BUTTONS ARE ADEQUATELY DIFFERENTIATED VIA MOUNTING ORIENTATION & LOCATION, MAKE/MODEL AND COLOUR OF BUTTON FROM THE UNDER-DESK MOUNTED PANIC RESET BUTTONS SUCH THAT THERE IS NO AMBIGUITY BETWEEN THE FUNCTIONS. IN ADDITION, THE PANIC BUTTON SHALL BE LABELED.
 - (S-2) AUDIBLE ANNUNCIATORS SHALL BE PROGRAMMED TO TRIGGER WHEN DOOR IS OPENED WITHOUT A VALID CREDENTIAL BEING PRESENTED AT THE CARD READER, AND WHEN DOOR IS HELD OPEN. COORDINATE WITH THE CLIENT REGARDING PROGRAMMING SPECIFICS.
 - (S-3) CAMERA HEADS SHALL BE POSITIONED TO CAPTURE DOORS 115K, 124 V, 125 AND 124S.
 - (S-4) CAMERA HEADS SHALL BE POSITIONED TO CAPTURE WAITING AREA 106 INCLUDING DOOR 106 AND CORRIDOR 115K. ARROWS INDICATE APPROXIMATE DIRECTION OF HEADS. COORDINATE CAMERA VIEWS WITH THE CLIENT.
 - (S-5) DEVICES CONNECTED TO HONEYWELL ACCESS CONTROL SYSTEM.
 - (S-6) DEVICES CONNECTED TO SALTO ACCESS CONTROL SYSTEM.

- ELECTRONIC SAFETY AND SECURITY GENERAL NOTES:
- THIS DRAWING SHALL BE READ IN CONJUNCTION WITH THE PROJECT RELATED DOOR HARDWARE SCHEDULE AS WELL AS THE PROJECT RELATED ARCHITECTURAL, ELECTRICAL AND MECHANICAL DRAWINGS.
 - ALL ITEMS SHOWN ARE BY THE SECURITY CONTRACTOR UNLESS OTHERWISE NOTED.
 - LOCATIONS OF DEVICES SHOWN ARE APPROXIMATE. COORDINATE THE EXACT LOCATION OF EACH DEVICE ON SITE WITH OTHER TRADES.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL ELECTRIFIED LOCKS AND DOOR CONTACTS WITH THE DOOR HARDWARE CONTRACTOR.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL POWER CIRCUITS WITH THE ELECTRICAL CONTRACTOR.
 - COORDINATE EXACT MOUNTING HEIGHTS AND LOCATIONS OF CCTV CAMERAS ON SITE WITH ELECTRICAL CONTRACTOR. PROVIDE ALL MOUNTING BRACKETS TO ENSURE THAT ALL OBSTRUCTIONS ARE AVOIDED AND CLEAR VIEW OF TARGET AREAS IS ATTAINED.
 - ALL CABLES SHALL BE HOME RUN IN CONDUITS. CABLE SPLICES SHALL NOT BE ACCEPTABLE. WHERE CABLES ARE GROUPED AND INSTALLED IN A SINGLE CONDUIT THE CONDUIT SHALL BE SIZED TO MAXIMUM 40% FULL.
 - REVIEW ALL PROJECT RELATED ARCHITECTURAL, MECHANICAL, ELECTRICAL, COMMUNICATIONS AND AV DRAWINGS AND SPECIFICATIONS. DESIGNER AND COORDINATE ALL OVERLAPPING WORK WITH SECURITY SYSTEMS TO AVOID COLLISIONS AND CONFLICTS OF DEVICES.
 - DEVICES SHALL NOT BE INSTALLED IN WALL AREAS THAT ARE DESIGNATED TO HAVE MARKER BOARD, FABRIC PANELS, OR ACCENT FINISHEDS UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - DEVICES SHALL NOT BE INSTALLED ABOVE ANY FURNITURE - AND SHALL BE LOCATED WHERE THERE IS ADEQUATE ACCESS FOR USE UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - INFORM THE ENGINEER'S REPRESENTATIVE AND QC OF ALL DEVICE AND FURNITURE CONFLICTS PRIOR TO INSTALLATION. OBTAIN RESOLUTION TO DEVICE AND FURNITURE CONFLICTS FROM THE ENGINEER'S REPRESENTATIVE PRIOR TO INSTALLATION.
 - REFER TO POWER AND SYSTEMS DRAWINGS FOR AUTOMATIC DOOR OPERATOR LOCATIONS. SECURITY CONTRACTOR SHALL COORDINATE SECURITY ACCESS CONTROL WITH ADD DOORS.

- DRAWINGS NOTES:
- (S-1) THE KITCHEN HOOD FIRE SUPPRESSION SYSTEM TO BASE BUILDING FIRE ALARM SYSTEM AS SEPARATE ZONE. ALLOW FOR UPDATING OF FIRE ALARM ZONE SCHEDULE.
 - (S-2) REFER TO POWER AND SYSTEMS DRAWINGS FOR AUTOMATIC DOOR OPERATOR LOCATIONS. SECURITY CONTRACTOR SHALL COORDINATE SECURITY ACCESS CONTROL WITH ADD DOORS.

KEY PLAN:

NORTH

REVISION	
NO.	DATE
1	2024-01-24
2	2024-11-15
3	2024-12-24
4	2024-12-23
5	2025-01-24
6	2025-01-31

Smith + Andersen

1100 - 109 Sheppard Ave East, Toronto ON, M2N 0N5
416-467-8151 smithandandersen.com

ENFORM architects

ENFORM Architects Inc.
1284 Sheppard Road, Suite 302B
Toronto, Ontario, Canada M8R 2B7
416-546-7523
www.enformarchitects.com

SEAL :

OWNER:

UNIVERSITY OF TORONTO

PROJECT:

HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:

LEVEL 01 - FIRE ALARM & SECURITY PLAN

PROJECT NUMBER:

21590.003

DRAWING SCALE:

1 : 100

DRAWN BY:

Author

CHECKED BY:

Checker

DATE:


Issue Date

SHEET NO.:

E501

REV.:

6




DRAWING NOTES:

- (S-1) REFER TO POWER AND SYSTEMS DRAWINGS FOR AUTOMATIC DOOR OPERATOR LOCATIONS. SECURITY CONTRACTOR SHALL COORDINATE SECURITY ACCESS CONTROL WITH ADO DOORS.
- (S-2) RELOCATE EXISTING SUPERVISORY VALVE AND FLOW SWITCH FOR SPRINKLER ZONE CONTROL CABINET TO NEW LOCATION SHOWN. COORDINATE FINAL LOCATION WITH MECHANICAL.

- SECURITY NOTES:
- (S-1) DEVICES CONNECTED TO HONEYWELL ACCESS CONTROL SYSTEM.
 - (S-2) DEVICES CONNECTED TO SALTO ACCESS CONTROL SYSTEM.
- ELECTRONIC SAFETY AND SECURITY GENERAL NOTES:
- THIS DRAWING SHALL BE READ IN CONJUNCTION WITH THE PROJECT RELATED DOOR HARDWARE SCHEDULE AS WELL AS THE PROJECT RELATED ARCHITECTURAL, ELECTRICAL AND MECHANICAL DRAWINGS.
 - ALL ITEMS SHOWN ARE BY THE SECURITY CONTRACTOR UNLESS OTHERWISE NOTED.
 - LOCATIONS OF DEVICES SHOWN ARE APPROXIMATE. COORDINATE THE EXACT LOCATION OF EACH DEVICE ON SITE WITH OTHER TRADES.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL ELECTRIFIED LOCKS AND DOOR CONTACTS WITH THE DOOR HARDWARE CONTRACTOR.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL POWER CIRCUITS WITH THE ELECTRICAL CONTRACTOR.
 - COORDINATE EXACT MOUNTING HEIGHTS AND LOCATIONS OF CCTV CAMERAS ON SITE WITH ELECTRICAL CONTRACTOR. PROVIDE ALL MOUNTING BRACKETS TO ENSURE THAT ALL OBSTRUCTIONS ARE AVOIDED AND CLEAR VIEW OF TARGET AREAS IS ATTAINED.
 - ALL CABLES SHALL BE HOME RUN IN CONDUITS. CABLE SPLICES SHALL NOT BE ACCEPTABLE. WHERE CABLES ARE GROUPED AND INSTALLED IN A SINGLE CONDUIT THE CONDUIT SHALL BE SIZED TO MAXIMUM 40% FILL.
 - REVIEW ALL PROJECT RELATED ARCHITECTURAL, MECHANICAL, ELECTRICAL, COMMUNICATIONS AND AV DRAWINGS AND SPECIFICATIONS. DESIGN AND COORDINATE ALL OVERLAPPING WORK WITH SECURITY SYSTEMS TO AVOID COLLISIONS AND CONFLICTS OF DEVICES.
 - DEVICES SHALL NOT BE INSTALLED ABOVE ANY FURNITURE AND SHALL BE LOCATED WHERE THERE IS ADEQUATE ACCESS FOR USE UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - DEVICES SHALL NOT BE INSTALLED ABOVE ANY FURNITURE AND SHALL BE LOCATED WHERE THERE IS ADEQUATE ACCESS FOR USE UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - INFORM THE ENGINEER'S REPRESENTATIVE AND QC OF ALL DEVICE AND FURNITURE CONFLICTS PRIOR TO INSTALLATION. OBTAIN RESOLUTION TO DEVICE AND FURNITURE CONFLICTS FROM THE ENGINEER'S REPRESENTATIVE PRIOR TO INSTALLATION.


- FIRE ALARM GENERAL NOTES:
- NEW SMOKE DETECTOR SHALL BE CONNECTED TO THE EXISTING BASE BUILDING ELEVATOR RECALL SYSTEM AND SHALL BE TIED INTO THE FIRE ALARM CONTROL PANEL. UPON ACTUATION OF A FIRE ALARM CONDITION ON THIS FLOOR THE FIRE ALARM PANEL SHALL SEND A RELAY TO THE ELEVATOR CONTROL PANEL FOR ELEVATOR AUTOMATIC RECALL SUCH THAT THE ELEVATOR RETURNS TO AN ALTERNATE FLOOR. PROVIDE ALL REQUIRED AUXILIARY CONTACTS AND RELAYS AT THE ELEVATOR CONTROL PANEL AND FIRE ALARM PANEL. ELECTRICAL CONTRACTOR TO COORDINATE ON SITE WITH LANDLORD AND ELEVATOR VENDOR FOR ALL REQUIREMENTS AND LOCATION OF EQUIPMENT. PROVIDE ALL REQUIRED FIRE ALARM VERIFICATION. ALL WORK TO COMPLY WITH CSA B44 LATEST EDITION TO THE SATISFACTION OF TSSA AND LOCAL AUTHORITIES HAVING JURISDICTION.
 - CONFIRM ELECTRICAL REQUIREMENTS AND EXACT LOCATION OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL DRAWINGS AND CONTRACTOR PRIOR TO ROUGH-INS.
 - ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
 - COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/QC DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.



REVISION	
NO.	DATE
1	2024-10-04
2	2024-11-15
3	2024-12-04
4	2024-12-23
5	2025-01-24
6	2025-01-31

- SECURITY NOTES:
- (S-1) DEVICES CONNECTED TO HONEYWELL ACCESS CONTROL SYSTEM.
 - (S-2) DEVICES CONNECTED TO SALTO ACCESS CONTROL SYSTEM.
- ELECTRONIC SAFETY AND SECURITY GENERAL NOTES:
- THIS DRAWING SHALL BE READ IN CONJUNCTION WITH THE PROJECT RELATED DOOR HARDWARE SCHEDULE AS WELL AS THE PROJECT RELATED ARCHITECTURAL, ELECTRICAL AND MECHANICAL DRAWINGS.
 - ALL ITEMS SHOWN ARE BY THE SECURITY CONTRACTOR UNLESS OTHERWISE NOTED.
 - LOCATIONS OF DEVICES SHOWN ARE APPROXIMATE. COORDINATE THE EXACT LOCATION OF EACH DEVICE ON SITE WITH OTHER TRADES.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL ELECTRIFIED LOCKS AND DOOR CONTACTS WITH THE DOOR HARDWARE CONTRACTOR.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL POWER CIRCUITS WITH THE ELECTRICAL CONTRACTOR.
 - COORDINATE EXACT MOUNTING HEIGHTS AND LOCATIONS OF CCTV CAMERAS ON SITE WITH ELECTRICAL CONTRACTOR. PROVIDE ALL MOUNTING BRACKETS TO ENSURE THAT ALL OBSTRUCTIONS ARE AVOIDED AND CLEAR VIEW OF TARGET AREAS IS ATTAINED.
 - ALL CABLES SHALL BE HOME RUN IN CONDUITS. CABLE SPLICES SHALL NOT BE ACCEPTABLE. WHERE CABLES ARE GROUPED AND INSTALLED IN A SINGLE CONDUIT THE CONDUIT SHALL BE SIZED TO MAXIMUM 40% FILL.
 - REVIEW ALL PROJECT RELATED ARCHITECTURAL, MECHANICAL, ELECTRICAL, COMMUNICATIONS AND AV DRAWINGS AND SPECIFICATIONS. DESIGN AND COORDINATE ALL OVERLAPPING WORK WITH SECURITY SYSTEMS TO AVOID COLLISIONS AND CONFLICTS OF DEVICES.
 - DEVICES SHALL NOT BE INSTALLED ABOVE ANY FURNITURE AND SHALL BE LOCATED WHERE THERE IS ADEQUATE ACCESS FOR USE UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - DEVICES SHALL NOT BE INSTALLED ABOVE ANY FURNITURE AND SHALL BE LOCATED WHERE THERE IS ADEQUATE ACCESS FOR USE UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - INFORM THE ENGINEER'S REPRESENTATIVE AND QC OF ALL DEVICE AND FURNITURE CONFLICTS PRIOR TO INSTALLATION. OBTAIN RESOLUTION TO DEVICE AND FURNITURE CONFLICTS FROM THE ENGINEER'S REPRESENTATIVE PRIOR TO INSTALLATION.

- FIRE ALARM GENERAL NOTES:
- NEW SMOKE DETECTOR SHALL BE CONNECTED TO THE EXISTING BASE BUILDING ELEVATOR RECALL SYSTEM AND SHALL BE TIED INTO THE FIRE ALARM CONTROL PANEL. UPON ACTUATION OF A FIRE ALARM CONDITION ON THIS FLOOR THE FIRE ALARM PANEL SHALL SEND A RELAY TO THE ELEVATOR CONTROL PANEL FOR ELEVATOR AUTOMATIC RECALL SUCH THAT THE ELEVATOR RETURNS TO AN ALTERNATE FLOOR. PROVIDE ALL REQUIRED AUXILIARY CONTACTS AND RELAYS AT THE ELEVATOR CONTROL PANEL AND FIRE ALARM PANEL. ELECTRICAL CONTRACTOR TO COORDINATE ON SITE WITH LANDLORD AND ELEVATOR VENDOR FOR ALL REQUIREMENTS AND LOCATION OF EQUIPMENT. PROVIDE ALL REQUIRED FIRE ALARM VERIFICATION. ALL WORK TO COMPLY WITH CSA B44 LATEST EDITION TO THE SATISFACTION OF TSSA AND LOCAL AUTHORITIES HAVING JURISDICTION.
 - CONFIRM ELECTRICAL REQUIREMENTS AND EXACT LOCATION OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL DRAWINGS AND CONTRACTOR PRIOR TO ROUGH-INS.
 - ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
 - COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/QC DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LEVEL 02 - FIRE ALARM &
SECURITY PLAN

PROJECT NUMBER:
21590.003

DRAWING SCALE:
1 : 100



DRAWN BY:
Author

CHECKED BY:
Checker

DATE:
Issue Date

SHEET NO.:
E502

REV:
6



REVISION	
NO.	DATE
1	2024-10-04
2	2024-11-15
3	2024-12-04
4	2024-12-23
5	2025-01-24
6	2025-01-31

- SECURITY GENERAL NOTES:
- (S-1) DEVICES CONNECTED TO HONEYWELL ACCESS CONTROL SYSTEM.
 - (S-2) DEVICES CONNECTED TO SALTO ACCESS CONTROL SYSTEM.
 - (S-3) CONDUIT ROUGH IN ONLY FOR FUTURE LOCK BY ELECTRICAL CONTRACTOR.
- ELECTRONIC SAFETY AND SECURITY GENERAL NOTES:
- THIS DRAWING SHALL BE READ IN CONJUNCTION WITH THE PROJECT RELATED DOOR HARDWARE SCHEDULE AS WELL AS THE PROJECT RELATED ARCHITECTURAL, ELECTRICAL AND MECHANICAL DRAWINGS.
 - ALL ITEMS SHOWN ARE BY THE SECURITY CONTRACTOR UNLESS OTHERWISE NOTED.
 - LOCATIONS OF DEVICES SHOWN ARE APPROXIMATE. COORDINATE THE EXACT LOCATION OF EACH DEVICE ON SITE WITH OTHER TRADES.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL ELECTRIFIED LOCKS AND DOOR CONTACTS WITH THE DOOR HARDWARE CONTRACTOR.
 - COORDINATE THE INSTALLATION AND INTERFACING WITH ALL POWER CIRCUITS WITH THE ELECTRICAL CONTRACTOR.
 - COORDINATE EXACT MOUNTING HEIGHTS AND LOCATIONS OF CCTV CAMERAS ON SITE WITH ELECTRICAL CONTRACTOR. PROVIDE ALL MOUNTING BRACKETS TO ENSURE THAT ALL OBSTRUCTIONS ARE AVOIDED AND CLEAR VIEW OF TARGET AREAS IS ATTAINED.
 - ALL CABLES SHALL BE HOME RUN IN CONDUITS. CABLE SPLICES SHALL NOT BE ACCEPTABLE. WHERE CABLES ARE GROUPED AND INSTALLED IN A SINGLE CONDUIT THE CONDUIT SHALL BE SIZED TO MAXIMUM 40% FILL.
 - REVIEW ALL PROJECT RELATED ARCHITECTURAL, MECHANICAL, ELECTRICAL, COMMUNICATIONS AND AV DRAWINGS AND SPECIFICATIONS. DETERMINE AND COORDINATE ALL OVERLAPPING WORK WITH SECURITY SYSTEMS TO AVOID COLLISIONS AND CONFLICTS OF DEVICES.
 - DEVICES SHALL NOT BE INSTALLED IN WALL AREAS THAT ARE DESIGNATED TO HAVE MARKER BOARD, FABRIC PANELS, OR ACCENT FINISHES UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - DEVICES SHALL NOT BE INSTALLED ABOVE ANY FURNITURE AND SHALL BE LOCATED WHERE THERE IS ADEQUATE ACCESS FOR USE UNLESS INDICATED SPECIFICALLY ON AN ELEVATED DRAWING.
 - INFORM THE ENGINEER'S REPRESENTATIVE AND QC OF ALL DEVICE AND FURNITURE CONFLICTS PRIOR TO INSTALLATION. OBTAIN RESOLUTION TO DEVICE AND FURNITURE CONFLICTS FROM THE ENGINEER'S REPRESENTATIVE PRIOR TO INSTALLATION.

- FIRE ALARM GENERAL NOTES:
- NEW SMOKE DETECTOR SHALL BE CONNECTED TO THE EXISTING BASE BUILDING ELEVATOR RECALL SYSTEM AND SHALL BE TIED INTO THE FIRE ALARM CONTROL PANEL. UPON ACTUATION OF A FIRE ALARM CONDITION ON THIS FLOOR THE FIRE ALARM PANEL SHALL SEND A RELAY TO THE ELEVATOR CONTROL PANEL FOR ELEVATOR AUTOMATIC RECALL SUCH THAT THE ELEVATOR RETURNS TO AN ALTERNATE FLOOR. PROVIDE ALL REQUIRED AUXILIARY CONTACTS AND RELAYS AT THE ELEVATOR CONTROL PANEL AND FIRE ALARM PANEL. ELECTRICAL CONTRACTOR TO COORDINATE ON SITE WITH LANDLORD AND ELEVATOR VENDOR FOR ALL REQUIREMENTS AND LOCATION OF EQUIPMENT. PROVIDE ALL REQUIRED FIRE ALARM VERIFICATION. ALL WORK TO COMPLY WITH CSA B44 LATEST EDITION TO THE SATISFACTION OF TSSA AND LOCAL AUTHORITIES HAVING JURISDICTION.
 - CONFIRM ELECTRICAL REQUIREMENTS AND EXACT LOCATION OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL DRAWINGS AND CONTRACTOR PRIOR TO ROUGH-INS.
 - ROUTE ALL CONDUIT SYSTEMS AROUND DUCT WORK, BEAMS AND PIPING AS REQUIRED TO ACCOMMODATE LAYOUT SHOWN. REFER TO MECHANICAL DRAWINGS AND ARCHITECTURAL DRAWINGS FOR ADDITIONAL DETAILS.
 - COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGN/OC DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.

- DRAWING NOTES:
- (N-1) INCLUDE IN THE COST FOR XTALIS SITE VISIT TO CONFIRM EXISTING SITE CONDITIONS TO PREPARE DOCUMENTATION REQUIRED FOR ADJUSTMENT OF XTALIS SYSTEM.
 - (N-2) PROVIDE AUXILIARY CONTACTS IN SMOKE DETECTOR SUCH THAT IT CAN SEND A SIGNAL TO FIRE SHUTTER CONTROL PANEL. PROVIDE 120V CONNECTION TO FIRE SHUTTER AND INSTALL UPDOWN CONTROL KEY SWITCH ON WALL TO CONTROL FIRE SHUTTER. COORDINATE WIRING REQUIREMENTS WITH OC AND FINAL LOCATION OF SWITCH ON SITE WITH ARCHITECTS. COORDINATE THIS WORK WITH BASE BUILDING FIRE ALARM CONTRACTOR AND INCLUDE FOR FIRE ALARM VERIFICATION OF DEVICES AND TIE-INS. FIRE SHUTTER TO BE HELD OPEN DURING NORMAL OPERATION AND CLOSE IN EVENT OF FIRE ALARM ACTIVATIONS OR ADJACENT SMOKE DETECTOR.
 - (N-3) REFER TO POWER AND SYSTEMS DRAWINGS FOR AUTOMATIC DOOR OPERATOR LOCATIONS. SECURITY CONTRACTOR SHALL COORDINATE SECURITY ACCESS CONTROL WITH ADD DOORS.
 - (N-4) MODIFY EXISTING VESDA SMOKE DETECTION SYSTEM IN ATRIUM AS SHOWN AS WELL AS THE RELOCATION OF THE CONTROL PANEL. ELECTRICIAN TO CONTACT XTALIS FOR REQUIRED SCOPE OF WORK AND TO INCLUDE ALL ASSOCIATED COSTS IN THE BID INCLUDING TESTING AND VERIFICATION.
 - (N-5) NEW DCP PANEL COMPATIBLE WITH BASE BUILDING FIRE ALARM SYSTEM. CONNECT TO EMERGENCY CIRCUIT.
 - (N-6) WALLS SHOWN IN THIS HATCHED AREA ARE FOR REFERENCE ONLY. SPACE WILL BE IN SHELL CONDITION.



Smith + Andersen
1100 - 109 Sheppard Ave East, Toronto, ON, M2N 0N5
416-467-8151 smithandandersen.com



ENFORM architects
ENFORM Architects Inc.
1284 Sheppard Road, Suite 302B
Toronto, Ontario, Canada M8R 2B7
416-546-7523
www.enformarchitects.com

SEAL :



PROJECT :
HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS :
LEVEL 03 - FIRE ALARM & SECURITY PLAN

PROJECT NUMBER : 21590.003	
DRAWING SCALE : 1 : 100	
DRAWN BY : Author	CHECKED BY : Checker
DATE : Issue Date	DATE : Issue Date
SHEET NO : E503	REV : 6

APPROXIMATE SNOW SENSOR

CASE 107A

ELEC 107B


SECTION A-A

TRENCH DRAIN SNOW-MELTING HEATING CABLE

SECTION B-B

Architectural drawing of a building facade showing a staircase and a large window. The drawing includes a section cut through the wall and floor, revealing the internal structure and the placement of snowmelt heating cables. Labels include 'SNOWMELT CONTROL', 'CONTROL PANEL FROM PANEL PP-MD', 'EX. GUFT. 101', 'TO TRENCH DRAIN SNOW MELTING HEATING CABLE', 'TO RAMP/FLOOR SNOW MELTING HEATING CABLE', and 'TO TRENCH MELTING'. The drawing is oriented vertically with a scale bar at the bottom.

SHEET NO : E600	REV : 6
---------------------------	-------------------



DRAWING NOTES:


- EXISTING UNDESIRABLE FEEDER/CONDUIT TO BE REMOVED.
- DISCONNECT AND REMOVE EXISTING WALL PACK COW WIRING BACK TO SOURCE AND MAKE SAFE. REUSE EXISTING CONDUITS PASSING THROUGH EXTERIOR WALL AND PROVIDE NEW BONES, CONDUITS, AND WIRING TO NEW EXTERIOR LIGHTING AS REQUIRED.

GENERAL NOTES:

- REFER TO THE INTERIOR DESIGNER'S ARCHITECT'S DRAWINGS TO DETERMINE COMPLETE EXTENT OF DEMOLITION AND ALLOW FOR ALL COSTS. COMPLETE EXTENT OF DEMOLITION IS NOT SHOWN.
- REMOVE ALL FLOOR, COLUMN, CEILING, AND WALL MOUNTED POWER, TELEPHONE/DATA OUTLETS, CABLING AND CONDUIT NOT REQUIRED TO SLUT NEW LAYOUT AND MAKE SAFE. VISIT SITE TO DETERMINE EXACT REQUIREMENTS AND REFER TO DEMOLITION DRAWINGS.
- MAKE GOOD ALL CORE HOLES FROM ELECTRICAL EQUIPMENT AND DEVICES DISCONNECTED, RELOCATED AND/OR REMOVED IN THIS PROJECT.
- REMOVE FLOOR MONUMENT(S) AND ALL ASSOCIATED CONDUIT(S) AND WIRE BACK TO SOURCE. MAKE GOOD ALL FLOOR PENETRATIONS TO COMPLY WITH CURRENT LOCAL APPLICABLE CODES.
- ENSURE THAT ALL EXISTING ELECTRICAL DEVICES, EQUIPMENT AND LIGHTING WITHIN BASE BUILDING ROOMS, STAIRWELLS AND AREAS DEEMED NOT IN SCOPE, REMAIN LIVE OPERATIONAL, ISOLATED AND PROTECTED DURING CONSTRUCTION.
- COORDINATE ALL WORK TO SLUT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGNER DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
- EXISTING CONDITIONS SHOWN ARE BASED ON DRAWINGS, FIELD SURVEY AND INFORMATION PROVIDED BY LANDLORD. ELECTRICAL CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BIDDING. ANY DISCREPANCIES BETWEEN EXISTING CONDITIONS AND THOSE SHOWN HERE SHALL BE BROUGHT TO THE ATTENTION OF THE PROJECT MANAGER PRIOR TO BIDDING.
- NO ADDITIONAL COST WILL BE APPROVED FOR ANY REVISIONS/MODIFICATIONS REQUIRED BY ANY TRADE OR CONTRACTOR DUE TO THE LACK OF COORDINATION BETWEEN TRADES AND CONTRACTORS.
- COORDINATE WITH GENERAL CONTRACTOR AND LANDLORD FOR DISPOSAL OF ALL MATERIALS FROM SITE.
- EXISTING FIRE ALARM DEVICES SHALL BE COILED AND FULLY FUNCTIONAL THROUGHOUT DEMOLITION CONSTRUCTION. NEW FIRE ALARM DEVICES SHALL BE PROVIDED AS PART OF NEW CONSTRUCTION PHASE. REFER TO PHASING SCHEDULE FOR CONSTRUCTION SCHEDULING.

- ELECTRICAL CONTRACTOR TO PROVIDE TEMPORARY EMERGENCY LIGHTING FOR ENTIRE SPACE TO ACCOMMODATE DEMOLITION WORK AND FUTURE BUILD-OUT. ENSURE FIXTURES ARE CHAIN HUNG AND SUPPORTED FROM THE CEILING SUBSTRUCTURE ABOVE.
- EXISTING EXT. SIGNS SHALL BE MAINTAINED THROUGHOUT DEMOLITION CONSTRUCTION. PROVIDE TEMPORARY SUPPORT FROM THE CEILING SUBSTRUCTURE ABOVE. NEW EXT. SIGNS SHALL BE PROVIDED AS PART OF NEW CONSTRUCTION PHASE.
- DEMOLISH EXISTING EMPTY CONDUITS WITHIN SCOPE OF WORK AREA.
- CONDUITS CONTAINING EXISTING FEEDER/WIRING SHALL BE REWIND.
- CONDUITS/FEEDERS MARKED FOR DEMOLITION SHALL BE VERIFIED TO BE UNUSED/EMPTY PRIOR TO DEMOLISHING.
- ALLOW FOR THE REROUTING OF EXISTING CONDUIT/FEEDERS TO ACCOMMODATE STRUCTURAL REPAIRS. TYPICAL OF TEN (10) CM DIA. 100' OF CONDUIT/FEEDERS.

KEY PLAN:



REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR FAS REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:

OWNER:



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
COFFLER


214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
**LEVEL 01 - ELECTRICAL -
DEMOLITION**

PROJECT NUMBER:
21590.003
DRAWING SCALE:
1 : 100

DRAWN BY: CHECKED BY: DATE:
Author Checker Issue Date

SHEET NO.: **E701** REV: **6**




DRAWING NOTES:
○ EXISTING UNDEEMPT FEEDER/CONDUIT TO BE REMOVED.

GENERAL NOTES:

- REFER TO THE INTERIOR DESIGNER'S ARCHITECT'S DRAWINGS TO DETERMINE COMPLETE EXTENT OF DEMOLITION AND ALLOW FOR ALL COSTS. COMPLETE EXTENT OF DEMOLITION IS NOT SHOWN.
- REMOVE ALL FLOOR, COLUMN, CEILING, AND WALL MOUNTED POWER, TELEPHONE/DATA OUTLETS, CABLEING AND CONDUIT NOT REQUIRED TO SUIT NEW LAYOUT AND MAKE SAFE. VISIT SITE TO DETERMINE EXACT REQUIREMENTS AND REFER TO DEMOLITION DRAWINGS.
- MAKE GOOD ALL CORE HOLES FROM ELECTRICAL EQUIPMENT AND DEVICES DISCONNECTED, RELOCATED AND/OR REMOVED IN THIS PROJECT.
- REMOVE FLOOR MONUMENT(S) AND ALL ASSOCIATED CONDUIT(S) AND WIRE BACK TO SOURCE. MAKE GOOD ALL FLOOR PENETRATIONS TO COMPLY WITH CURRENT LOCAL APPLICABLE CODES.
- ENSURE THAT ALL EXISTING ELECTRICAL DEVICES, EQUIPMENT AND LIGHTING WITHIN BASE BUILDING ROOMS, STAIRWELLS AND AREAS DEEMED NOT IN SCOPE, REMAIN IN OPERATIONAL, ISOLATED AND PROTECTED DURING CONSTRUCTION.
- COORDINATE ALL WORK TO SUIT PROJECT PHASE SCHEDULE. COORDINATE PHASING WITH ARCHITECT/INTERIOR DESIGNER DRAWINGS. PHASING IF SHOWN IS FOR REFERENCE PURPOSES ONLY.
- EXISTING CONDITIONS SHOWN ARE BASED ON DRAWINGS, FIELD SURVEY AND INFORMATION PROVIDED BY LANDLORD. ELECTRICAL CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BIDDING. ANY DISCREPANCIES BETWEEN EXISTING CONDITIONS AND THOSE SHOWN HERE SHALL BE BROUGHT TO THE ATTENTION OF THE PROJECT MANAGER PRIOR TO BIDDING.
- NO ADDITIONAL COST WILL BE APPROVED FOR ANY REVISIONS/MODIFICATIONS REQUIRED BY ANY TRADE OR CONTRACTOR DUE TO THE LACK OF COORDINATION BETWEEN TRADES AND CONTRACTORS.
- COORDINATE WITH GENERAL CONTRACTOR AND LANDLORD FOR DISPOSAL OF ALL MATERIALS FROM SITE.
- EXISTING FIRE ALARM DEVICES SHALL BE COILED AND FULLY FUNCTIONAL THROUGHOUT DEMOLITION CONSTRUCTION. NEW FIRE ALARM DEVICES SHALL BE PROVIDED AS PART OF NEW CONSTRUCTION PHASE. REFER TO PHASING SCHEDULE FOR CONSTRUCTION SCHEDULING.

- ELECTRICAL CONTRACTOR TO PROVIDE TEMPORARY EMERGENCY LIGHTING FOR ENTIRE SPACE TO ACCOMMODATE DEMOLITION WORK AND FUTURE BUILDOUT. ENSURE FIXTURES ARE CHAIN HUNG AND SUPPORTED FROM THE CEILING SLAB/STRUCTURE ABOVE.
- EXISTING EXIT SIGNS SHALL BE MAINTAINED THROUGHOUT DEMOLITION CONSTRUCTION. PROVIDE TEMPORARY SUPPORT FROM THE CEILING SLAB/STRUCTURE ABOVE. NEW EXIT SIGNS SHALL BE PROVIDED AS PART OF NEW CONSTRUCTION PHASE.
- DEMOLISH EXISTING EMPTY CONDUITS WITHIN SCOPE OF WORK AREA.
- CONDUITS CONTAINING EXISTING FEEDER/WIRING SHALL BE REWIRED.
- CONDUITS/FEEDERS MARKED FOR DEMOLITION SHALL BE VERIFIED TO BE UNDEEMPT PRIOR TO DEMOLISHING.
- ALLOW FOR THE REROUTING OF EXISTING CONDUIT/FEEDERS TO ACCOMMODATE STRUCTURAL REPAIRS. TYPICAL OF TEN (10) OR 100' OF CONDUIT/FEEDERS.

KEY PLAN:



REVISION

NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50% PERMIT
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR FAS REVIEW
4	2024-12-23	ISSUED FOR FAS REVIEW
5	2025-01-24	ISSUED FOR FAS REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:



PROJECT:
**HEALTH AND WELLNESS
CENTRE RENOVATION AT
COFFLER**

214 COLLEGE ST.
TORONTO, ON M5T 3A1


SHEET CONTENTS:
**LEVEL 02 - ELECTRICAL -
DEMOLITION**

PROJECT NUMBER:
21590.003
DRAWING SCALE:
1 : 100

DRAWN BY: CHECKED BY: DATE:
Author Checker Issue Date

SHEET NO.: **E702** REV: **6**





ENFORM
architects

ENFORM Architects Inc.
128A Sterling Road, Suite 302B
Toronto, Ontario, Canada M6R 2B7
t: 647-948-7523
www.enformarchitects.com

Al :	
------	--



PROJECT:
HEALTH AND WELLNESS
CENTRE RENOVATION AT
KOFFLER

14 COLLEGE ST,
TORONTO, ON M5T 3A1


**LEVEL 01 EXISTING CONDUIT
PLAN (FOR REFERENCE)**

PROJECT NUMBER:
1590.003

DRAWING SCALE:
1:300

DRAWN BY : Author	CHECKED BY : Checker	DATE: Issue Date
----------------------	-------------------------	---------------------

SHEET NO : **E705** REV : **6**



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-04	ISSUED FOR F&S REVIEW
4	2024-12-23	ISSUED FOR F&S REVIEW
5	2025-01-24	ISSUED FOR PEER REVIEW
6	2025-01-31	ISSUED FOR BID



ENFORM Architects Inc.
128A Sterling Road, Suite 302B
Toronto, Ontario, Canada M6R 2B7
t: 647-948-7523
www.enformarchitects.com

OWNERS





214 COLLEGE ST.
TORONTO, ON M5T 3A1

PROJECT NUMBER :	21590.003
DRAWING SCALE :	

SHEET NO :	REV
E706	6

6



REVISION		
NO.	DATE	DESCRIPTION
1	2024-10-04	ISSUED FOR 50%
2	2024-11-15	PERMIT
3	2024-12-24	ISSUED FOR P&S REVIEW
4	2024-12-23	ISSUED FOR P&S REVIEW
5	2025-01-24	ISSUED FOR P&S REVIEW
6	2025-01-31	ISSUED FOR BID



SEAL:	
-------	--



PROJECT:
HEALTH AND WELLNESS CENTRE RENOVATION AT KOFFLER

214 COLLEGE ST.
TORONTO, ON M5T 3A1

SHEET CONTENTS:
LEVEL 03 EXISTING CONDUIT PLAN (FOR REFERENCE)

PROJECT NUMBER: 21590.003		
DRAWING SCALE: 1 : 500		
DRAWN BY: Author	CHECKED BY: Checker	DATE: Issue Date
SHEET NO.: E707	REV: 6	