265000_LUMINAIRE SCHEDULE

TYPE	VOLTS	LAMP (QTY)	DESCRIPTION	MFR.TYPE/SERIES
L01	120	LED 3500K, MINIMUM 80 CRI	4' LED suspended strip light, 4000lm	Metalux SNLED or equivalent
L02	120	LED 3500K, MINIMUM 80 CRI	Surface Mount Linear LED, aluminium, black, low glare optic, 6ft length, medium output	Lumenwerx via 3 surface or equivalent,
L02B	120	LED 3500K, MINIMUM 80 CRI	Surface Mount Linear LED, aluminium, black, low glare optic,8ft length,medium output	Lumenwerx via 3 surface or equivalent,
L02C	120	LED 3500K, MINIMUM 80 CRI	Surface Mount Linear LED, aluminium, black, low glare optic,4ft length, medium output	Lumenwerx via 3 surface or equivalent,
L03	120	LED 3500K, MINIMUM 80 CRI	4 inch LED Recessed Round Downlight, 3000lm, 40 deg	EcoNU4RD-SW-20-35K-80-HE40-120-NC-WH-WH or equivalent
L04	120	LED 3500K, MINIMUM 80 CRI	2' x 2' LED Recessed Ceiling Panel, 4000lm	Metalux SNLED or equivalent
L05	120	LED 3500K, MINIMUM 80 CRI	4 inch LED Recessed Round Downlight, 3000lm, 40deg, Anti Ligature and impact resistance	Alko 4" Behavioural Health Downlight or equivalent
L06	120	LED 3500K, MINIMUM 80 CRI	Surface mount undercounter LED luminaire, length to suit millwork, 234LM/ft	Kendo S Static Surface or equivalent
X01	120	LED	Exit Sign, Aluminum Housing, LED, Single Or Double Face, Back-to-Wall, End-to-Wall, pendant or Ceiling Mounted As Shown on Drawings, Green Running Man Pictogram, White Housing	Lumacell LA Series Beghelli Micra RM Series Aimlite RPALW Series