

265000_LUMINAIRE SCHEDULE

TYPE	VOLTS	LAMP (QTY)	DESCRIPTION	MFR.TYPE/SERIES
L01	120	LED 3500K, MINIMUM 80 CRI	2' x 4' LED Recessed Ceiling Panel, 4000lm	Peer Lux PNLV Lithonia CPX Metalux 22FP
L02	120	LED 3500K, MINIMUM 80 CRI	4' LED Wall mount strip light, 160w/lm, 4000lm	Metalux SNLED or equivalent
L03	120	LED 3500K, MINIMUM 80 CRI	1' x 4' LED Recessed Ceiling Panel, 3000lm	Peer Lux PNLV Lithonia CPX Metalux 22FP
L04	120	LED 3500K, MINIMUM 80 CRI	4 inch LED Recessed Round Downlight, 2000lm, 40 deg	EcoNU4RD-SW-20-35K-80-HE40-120-NC-WH- WH or equivalent
L05	120	LED 3500K, MINIMUM 80 CRI	8' LED Surface Mount strip light, 9600lm, round,clear lens	Metalux SNLED or equivalent
L06	120	LED 3500K, MINIMUM 80 CRI	4' Surface Mount strip light, 2200lm, round, semi frost lens, narrow	Metalux SNLED or equivalent
L07	120	LED 3500K, MINIMUM 80 CRI	Linear Pendant, length to suit drawing, flush lens, 400 lumens per foot, 10% dimming, 120V, white finish	Mark Lighting, Slot 2 Pendant or equivalent
L08	120	LED 3500K, MINIMUM 80 CRI	2' x 2' LED Recessed Ceiling Panel, 4000lm	Peer Lux PNLV Lithonia CPX Metalux 22FP
L09			UNUSED	
L10			Undercabinet Striplight, length to suit cabinet geometry. Clip mounting to underside of cabinet. See architectural millwork detail for mounting geometry. Provide 4 output driver mounted under cabinet near wall plug.	Vode Zipone or equivalent
X01		LED	Exit Sign, Aluminum Housing, LED, Single Or Double Face, Back-to-Wall, End-to-Wall, pendant or Ceiling Mounted As Shown on Drawings, Green Running Man Pictogram, White Housing	Lumacell LA Series Beghelli Micra RM Series Aimlite RPALW Series
X02		LED	Exit Sign, Aluminum Housing, LED, Single Or Double Face, Back-to-Wall, End-to-Wall, pendant or Ceiling Mounted As Shown on Drawings, Green Running Man Pictogram, White Housing, C/W battery pack and remote heads	Lumacell LA Series Beghelli Micra RM Series Aimlite RPALW Series

265000_LUMINAIRE SCHEDULE

TYPE	VOLTS	LAMP (QTY)	DESCRIPTION	MFR.TYPE/SERIES
B01	120	6W LED	Emergency Battery Unit, 120 Volt Input, 12 Volt Output, Minimum 100 Watt Capacity For 30 minute for connected load, Enclosed In EEMAC 1 Code Gauge Steel Housing, 10 Year Life, Time Delay Relay, Voltmeter, Two Integral 6 Watt LED MR16 Heads	Lumacell Signature Series LD10 Heads, Lumacell RG12S Series or approved equal
B02	120	6W LED	Emergency Remote heads, Two 6 Watt LED LD10 Heads	Lumacell Signature Series LD10 Heads, or approved equal