

265000_LUMINAIRE SCHEDULE				
TYPE	VOLTS	LAMP (QTY)	DESCRIPTION	MFR.TYPE/SERIES
L01	120	LED 3500K, MINIMUM 80 CRI	ROUND LED HIGH BAY LUMINAIRE, SURFACE MOUNT TO UNDERSIDE OF JOIST/TRUSS, 12,000 LUMEN	METALUX UHB LED HIGH BAY or equivalent
L02	120	LED 3500K, MINIMUM 80 CRI	4' LED Wall mount strip light, 160w/lm, 4000lm	Metalux SNLED or equivalent
L03	120	LED 3500K, MINIMUM 80 CRI	2' x 4' LED Recessed Ceiling Panel, 4000lm	Peer Lux PNLV Lithonia CPX Metalux 22FP
L04	120	LED 3500K, MINIMUM 80 CRI	2' x 2' LED Recessed Ceiling Panel, 2000lm	Peer Lux PNLV Lithonia CPX Metalux 22FP
L05	120	LED 3000K, MINIMUM 80 CRI	LED Pendant Mount Architectural, Round 4500lm, medium distribution. Brushed Aluminium, hug via aircraft cable	Acuity Shaper 1800 Series or equivalent
X01	120	LED	Exit Sign, Aluminum Housing, LED, Single Or Double Face, Back-to- Wall, End-to-Wall, pendant or Ceiling Mounted As Shown on Drawings,	Lumacell LA Series Beghelli Micra RM Series
X02	120	LED	Exit Sign, Aluminum Housing, LED, Single Or Double Face, Back-to- Wall, End-to-Wall, pendant or Ceiling Mounted As Shown on Drawings, Green Running Man Pictogram, White Housing, C/W battery pack and remote heads	Lumacell LA Series Beghelli Micra RM Series Aimlite RPALW Series
B01	120	6W LED MR16	Emergency Battery Heads, 120 Volt Input, 12 Volt Output,	Lumacell Signature Series LD10 Heads
B02	120	6W LED MR16	Emergency Battery Unit, 120 Volt Input, 12 Volt Output, Minimum 100 Watt Capacity For 30 minute for connected load, Enclosed In EEMAC 1 Code Gauge Steel Housing, 10 Year Life, Time Delay Relay, Voltmeter, Two Integral 6 Watt LED MR16 Heads	Lumacell Signature Series LD10 Heads, Lumacell RG12S Series or approved equal